

HIGHTEC VINTAGE SAE 50 UNLEGIERT

Unblended, mineral-based, monograde engine oil of viscosity grade SAE 50.

Description

HIGHTEC VINTAGE SAE 50 UNLEGIERT is a monograde engine oil of SAE grade 50 produced using selected mineral base oils. Eminently suitable for use in historic Otto and diesel engines without turbocharging.

Application

HIGHTEC VINTAGE SAE 50 UNLEGIERT is successfully used in engines and gearboxes of vintage or veteran passenger cars and classic vehicles that require oil without additional additives (= unblended). HIGHTEC VINTAGE SAE 50 UNLEGIERT is based on well-refined base oils and ensures fewer deposits and wear with its high flash point, marginal evaporation loss and low ash content.

Specifications

- API SA

Advantages

- Stable lubricating film, even with hot oil and under high loads
- Prevention of adhesion, lacquering and coking of cylinders, pistons and valves
- Suitable for engines without filters
- Very good seal compatibility
- Miscible and compatible with mineral-based and synthetic engine oils. However, in order to exploit the full product benefits of HIGHTEC VINTAGE SAE 50 UNLEGIERT, a complete oil change is recommended.



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.895
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	18,3
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	213,7
Viscosity index	ASTM D2270	-	95
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	278
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-13

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

