

## HIGHTEC VINTAGE SAE 40 MILD LEGIERT

Semi-blended, monograde engine oil for vintage and classic cars based on mineral base oils.

### Description

HIGHTEC VINTAGE SAE 40 MILD LEGIERT is a monograde engine oil of SAE grade 40 produced using selected base oils.

### Application

HIGHTEC VINTAGE SAE 40 MILD LEGIERT is used successfully in vintage and classic cars equipped with Otto and diesel engines according to the manufacturer's specification. The premium base oils and the adjusted additive composition with a high zinc content prevent deposits, wear and leaks, as well as material incompatibilities. HIGHTEC VINTAGE SAE 40 MILD LEGIERT is most commonly used for operation at summer temperatures. HIGHTEC VINTAGE SAE 40 MILD LEGIERT is also used in gearboxes, provided that the manufacturer recommends the use of an appropriate engine oil.

### Equivalent quality in accordance with EU-law as per

- API SF/CD

### Advantages

- Outstanding material compatibility
- High zinc content for safe wear protection
- Prevention of adhesion, lacquering and coking of cylinders, pistons and valves
- Appropriate viscosity grade for summer operation
- Stable lubricating film, even with hot oil and under high loads
- Low evaporation losses ensure low oil consumption
- High level of oxidation protection by means of selected base oils
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of HIGHTEC VINTAGE SAE 40 MILD LEGIERT, a complete oil change is recommended.

ROWE MINERALÖLWERK GMBH  
Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle?  
Scan this code for the ROWE-oilfinder.

## Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.9
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	15,7
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	173,4
Viscosity index	ASTM D2270	-	92
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	260
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-19
Total base number	DIN 51639-1	mgKOH/g	6,1
Zinc-content		ppm Zn	1000

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply ([www.rowe-oil.com](http://www.rowe-oil.com)).

