

HIGHTEC MARINE POWER HFO 50 SAE 40

HIGHTEC MARINE POWER HFO 50 SAE 40 is a multifunctional trunk piston engine oil.

Description

HIGHTEC MARINE POWER HFO 50 SAE 40 is a multifunctional trunk piston engine oil for highly rated medium-speed diesel engines running on residual fuel and build before 2010.

Application

HIGHTEC MARINE POWER HFO 50 SAE 40 is designed for medium-speed industrial or marine propulsion and auxiliary engines which are burning residual fuel.

Equivalent quality in accordance with EU-law as per

- API CF
- Caterpillar
- Daihatsu
- MAN Diesel
- MAN Turbo
- Wärtsilä
- Yanmar



Typical characteristics

| Property | Method | Unit | Value |
|----------------------------|-----------------------------|--------------------|-------|
| Density at 15 °C | ASTM D-7042 | g/ml | 1 |
| Kinematic viscosity KV 100 | ASTM D-7042 | mm ² /s | 14,5 |
| Kinematic viscosity KV 40 | ASTM D-7042 | mm ² /s | 141 |
| Viscosity index | ASTM D2270 | - | 101 |
| Flash point | ASTM D-92 / DIN EN ISO 2592 | °C | 225 |
| Total base number | DIN 51639-1 | mgKOH/g | 50 |

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

