

## HIGHTEC MARINE 12 SAE 40

HIGHTEC MARINE 12 SAE 40 is a multifunctional trunk piston engine oil.

### Description

HIGHTEC MARINE 12 SAE 40 is a multifunctional trunk piston engine oil for highly rated diesel engines operated on distillate fuel.

### Application

HIGHTEC MARINE 12 SAE 40 is designed for medium speed trunk piston engines operating on distillate fuels. For use in the latest generation of medium-speed 4-stroke trunk piston engines as well as older engine types.

### Equivalent quality in accordance with EU-law as per

- API CF
- Daihatsu
- Yanmar

### Advantages

- Very good engine cleanliness
- Resists thermal & oxidative stress
- Advanced high temperature deposit control
- Strong TBN retention



## Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	1
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	14,3
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	118,0
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	270
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-15
Total base number	DIN 51639-1	mgKOH/g	12,0

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply ([www.rowe-oil.com](http://www.rowe-oil.com)).

