

## HIGHTEC SKM

HIGHTEC SKM is a mineral saw chain oil of ISO VG grade 100.

### Description

HIGHTEC SKM saw chain oil is recommended for lubricating chainsaws from reputable manufacturers.

### Application

HIGHTEC SKM has large power reserves that guarantee less wear and thus a longer service life for the saw chain, even under adverse operating conditions. The saw chain oil HIGHTEC SKM retains the highest level of wear protection and its slightly thixotropic characteristics due to selected additives.

### Advantages

- High level of wear protection
- Adherent ('thixotropic')
- Suitable for all applications



## Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.887
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	100
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	> 210
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-18

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply ([www.rowe-oil.com](http://www.rowe-oil.com)).

