

HIGHTEC ANTIFREEZE COOLANT AN 12 EVO READY-MIX -37 °C

Ready-to-use premium long-life coolant based on monoethylene glycol with high corrosion and frost protection. Nitrite, amine and phosphate free. Reliable protection for aluminum and cast iron engines.

Description

Equivalent quality in accordance with EU-law as per

- ASTM D3306
- ASTM D4985
- BS 6580:2010
- CUNA NC 956-16
- JIS K 2234:2006
- SAE J1034
- SANS 1251:2005
- Cummins CES 14603/14439
- Deutz DQC CC-14
- VW TL 774-G(12+)/J(G13)/L(G12Evo)

This product is also recommended when the following filling instructions are required

- AS 2108-2004
- ASTM D6210
- China GB 29743-2013
- BMW LC-18(83 19 2 466 484/83 19 2 468 442/83 19 2 468 443)/LC-87(83 19 2 211 191/83 51 2 355 290/83 19 2 211 194/83 19 2 211 913/83 19 2 211 195/83 19 2 211 914)
- Deutz DQC CA-14/CB-14
- DTFR 29C100 (ex. MB 325.0)
- Fiat 9.55523
- Ford ESD-M97B49-A
- Iveco 18-1830
- MAN 324 NF/324 SNF/324 Si-OAT
- MTU MTL 5048
- Toyota Long Life Coolant 1WW/2WW
- VW TL 774-C(G11)/D(G12)/F(G12+)



Typical characteristics

Property	Method	Unit	Value
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	> 100
Density at 20 °C	ASTM D1122	g/ml	1.07
pH	ASTM D1287	-	8,3

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

