PRODUCT INFORMATION

ROWE®

HIGHTEC ATF 9007

High-performance ATF with reduced viscosity for efficient operation.

Description

HIGHTEC ATF 9007 is a high-performance ATF with reduced viscosity, formulated with state-of-the-art additives and a special base oil blend of the latest HC synthetic oils. It is specifically designed for use in modern 9-speed automatic transmissions, such as those found in SUVs, mid-range, and luxury vehicles. The reduced viscosity and optimized viscosity-temperature behavior ensure efficient operation.

Application

HIGHTEC ATF 9007 has been adapted to meet the specific requirements of modern 9-speed automatic transmissions, such as the 9G-TRONIC from Mercedes-Benz. It is used here in accordance with the manufacturer's specifications, and its specific coefficient of friction ensures slip-free power transmission even at very high engine torque, enabling spontaneous and sporty shifting without compromising comfort. The excellent consistency of the coefficient of friction guarantees consistent shifting performance throughout the entire shift interval.

Specifications

- JASO 1A-LV

ROWE recommendations

- DSIH 6p805
- Hyundai/Kia SPH-IV, SP-IV RR
- Hyundai NWS-9638
- MB 236.17, MB 236.16
- Mitsubishi J3,PA, SP-IV
- Nissan Matic W
- Saab 93165147
- Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675)
- VW G 055 162, G 052 540

Advantages

- Reduced viscosity for efficient operation
- Excellent consistency in coefficient of friction throughout the entire oil change interval, resulting in maximum driving and shifting comfort
- Best-in-class wear protection properties for reliable performance and maximum service life
- Excellent low-temperature shifting performance
- Outstanding aging and oxidation stability
- Minimized foaming tendency
- Neutral toward seal materials
- Miscible and compatible with other ATFs of the same specification. However, to fully realize the product benefits of HIGHTEC ATF 9007, a complete oil change is strongly recommended.

Notes

- Not suitable for use in DCT/DSG (dual-clutch) or CVT (continuously variable) transmissions.

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms

Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.

PRODUCT INFORMATION

ROWE®

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.846
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	6,2
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	30,8
Viscosity index	ASTM D2270	-	156
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	231
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms

Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.