PRODUCT INFORMATION



HIGHTEC HVLP 68 ZAF (HF-0)

Multi-purpose lubricating oil for hydraulics, industrial gears and bearings

Description

HIGHTEC HVLP 68 ZAF (HF-0) is a hydraulic oil that contains additives to prevent corrosion, wear and friction.

HIGHTEC HVLP 68 ZAF (HF-0) contains agents that ensure clean hydraulics.

 $\dot{\text{HIGHTEC}}$ HVLP 68 ZAF (HF-0) has a high viscosity index that facilitates use, even at colder external temperatures.

HIGHTEC HVLP 68 ZAF (HF-0) is a multi-purpose lubricating oil with a high load-bearing capacity that improves performance in mixed-friction conditions, thus counteracting friction or frictional vibrations due to stick-slip.

A special focus should therefore be placed on its good wear protection and cleaning properties as well as its good sludge carrying capacity.

HIGHTEC HVLP 68 ZAF (HF-0) exceeds the requirements concerning HLP hydraulic oils in compliance with DIN 51524 Part 3 for hydraulics.

Advantages

- · High level of wear protection
- · Zinc-free and ash-free
- First-rate VT performance
- · Good corrosion protection
- Thermally stable
- · Resistant to oxidation
- · Good air separation ability and foaming behaviour
- Hydrolytic resistance

Recommendation

Field of application: - Machine tools, construction and textile machinery - Run-in oil for units and machines - Oil for functional tests - Break-in oil, also for overseas exports in the event of wet deliveries - Electrical multi-plate clutches - Foundries - Cement factories - Hydraulics used in agriculture

ROWE MINERALÖLWERK GMBH Langgewann 101, D-67547 Worms



PRODUCT INFORMATION



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.867
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	10,8
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	68
Viscosity index	ASTM D2270	-	148
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>200
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-39

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH Langgewann 101, D-67547 Worms

