

## HIGHTEC HLP-D 32 HVI

Detergent/dispersive, multigrade hydraulic oil with a high viscosity index (VI) for hydraulics, industrial gears and bearings

### Description

HIGHTEC HLP-D 32 HVI is a detergent hydraulic oil containing additives to prevent corrosion, wear and friction. HIGHTEC HLP-D 32 HVI has a high viscosity index that facilitates use, even at colder external temperatures. HIGHTEC HLP-D 32 HVI contains agents that ensure clean hydraulics at all times. HIGHTEC HLP-D 32 HVI is a multi-purpose lubricating oil with a high load-bearing capacity that improves performance in mixed-friction conditions, thus counteracting friction or frictional vibrations due to stick-slip. A special focus should be placed on its good wear protection and cleaning properties as well as its good sludge carrying capacity. HIGHTEC HLP-D 32 HVI exceeds the requirements concerning hydraulic oils in compliance with DIN 51524 Part 3. The non-standardised designation HLP-D describes detergent hydraulic oils, where D provides an indication of the detergent properties.

### Equivalent quality in accordance with EU-law as per

- DIN 51524, p. 3 (HVLP)
- VDMA 24318
- SEB 181-222

### Advantages

- High level of wear protection
- Good detergent and dispersion characteristics
- First-rate VT performance
- Good corrosion protection
- Thermally stable
- Resistant to oxidation
- Good air separation ability and foaming behaviour
- Hydrolytic resistance

### Recommendation

- Break-in oil, also for overseas exports in the event of wet deliveries - Electrical multi-plate clutches - Cement factories - Construction machinery - Hydraulics used in agriculture - Generally employed for hydraulics in outdoor areas



## Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.863
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	6,2
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	32
Viscosity index	ASTM D2270	-	146
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	218
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-42

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply ([www.rowe-oil.com](http://www.rowe-oil.com)).

