# PRODUCT INFORMATION



# **HIGHTEC BIO HLP 46 S**

Environmentally-friendly, readily biodegradable hydraulic oil based on synthetic esters for all hydraulic systems.

## **Description**

HIGHTEC BIO HLP 46 S is an environmentally safe alternative to mineral oil-based hydraulic oils. The product is readily biodegradable according to MITI. It is insoluble in water and is largely held in the earth's upper layers after leaks or oil spills, such as when oil leaks from a broken pipeline, and rapidly degraded there.

## Equivalent quality in accordance with EU-law as per

• ISO 15380

#### **Advantages**

- · Very high viscosity index, multigrade characteristics
- Very high flash point
- High operating temperatures of up to 130°C at the upper limit
- · Readily biodegradable
- Environmentally-friendly

#### Recommendation

HIGHTEC BIO HLP 46 S should be used wherever there is a risk of leaking hydraulic fluid entering the groundwater or wastewater. This includes all devices that operate in water purification and water protection areas or near surface water, such as: - Wastewater treatment plants - Dredging vessels and floating dredgers - Hydraulic units in woods and fields - Earth-moving machines in water catchment areas - Pipe jacking and tunnel boring - Watergate lock hydraulics and stream weirs. HIGHTEC BIO HLP 46 S can be used for any application where oils of the following grades are already in use: HLP 32, HLP 46, HLP 68, HVLP 46, HEES 46.

#### **Notes**

• HIGHTEC BIO HLP 46 S is miscible with mineral oils. Store the product in a dry and frost-free environment.

**ROWE MINERALÖLWERK GMBH** Langgewann 101, D-67547 Worms



# PRODUCT INFORMATION



## **Typical characteristics**

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.912
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	9,2
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	46
Viscosity index	ASTM D2270	-	187
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>300
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36
Renewable Resource Content		%	>70
FZG A/8.3/90 (min)	DIN 51354/2	SKS	>12

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

**ROWE MINERALÖLWERK GMBH** Langgewann 101, D-67547 Worms

