PRODUCT INFORMATION



HIGHTEC FORK OIL 10W HC

High-performance fork oil based on HC synthetic oils.

Description

HIGHTEC FORK OIL 10W HC is a high-performance fork oil based on HC synthetic oils with first-rate low-temperature performance and superior damping properties. In addition, this product is characterised by a high resistance to ageing

Application

HIGHTEC FORK OIL 10W HC has been developed specifically for use in motorcycle forks and shock absorbers. Its first-rate viscositytemperature behaviour guarantees safe operation at high steadystate temperatures, as well as a sensitive response at very low temperatures.

Advantages

- · Outstanding viscosity-temperature behaviour and high shear
- Sensitive response characteristics, even at extremely low temperatures
- The highest ageing and oxidation stability due to special HC synthetic base oils
- The best wear protection properties for reliable operation and the longest service life, even at high steady-state temperatures and under excessive loads
- Minimal tendency to foam
- Reliable protection against corrosion, wear, sludge accumulation and adhesion
- Neutral behaviour towards gasket materials Miscible and compatible with other fork oils of the same specification. However, in order to exploit the full product benefits of HIGHTEC FORK OIL 10W HC, a complete oil change is strongly recommended.

Notes

· HIGHTEC FORK OIL 10W HC may not be mixed with glycol or silicone-based fluids (e.g. brake fluids DOT 3/4/5.1 or DOT 5).

> **ROWE MINERALÖLWERK GMBH** Langgewann 101, D-67547 Worms



PRODUCT INFORMATION



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.838
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	6,15
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	33,5
Viscosity index	ASTM D2270	-	134
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	250
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH Langgewann 101, D-67547 Worms

