

HIGHTEC SUNLUB® LONGLIFE 68

Description

Fully synthetic, high-performance hydraulic oil developed for an extra-long oil service life and high system protection. Based on high-quality polyalphaolefins (PAO). Awarded the EU Ecolabel.



Approvals

- EU Ecolabel NL/027/011

Specifications

- DIN 51524-3 HVLP
- ISO 15380 HEPR



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.85
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	10,9
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	63,6
Viscosity index	ASTM D2270	-	164
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>200
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-30
Biodegradability	OECD 301 B	%	>60
FZG A/8.3/90 (min.)	DIN 51351/2	SKS	>12

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.