

HIGHTEC SUNLUB® GRIND 7 ECO

Description

High Performance Bio cutting oil. Non-water-miscible coolant for cutting and grinding. Awarded with the EU Ecolabel.



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.861
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	2,3
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	6,9
Viscosity index	ASTM D2270	-	182
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	200
Foaming behaviour at 24°C	ASTM D 892	ml/ml	20/0
Foaming behaviour at 93.5°C	ASTM D 892	ml/ml	15/0
Foaming behaviour at 24°C to 93.5°C	ASTM D 892	ml/ml	25/0
Corrosion effect on copper	DIN 51 811	Grad	1a
Biodegradability	OECD 301 B	%	>60

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

