

HIGHTEC GREASEGUARD Ca-MN 2

Description

Semi-synthetic calcium special grease with corrosion and oxidation inhibitors. Good pressure absorption capacity due to EP additives.

Equivalent quality in accordance with EU-law as per

- DIN 51 502/51 825: KP 2 K-30
- T[°C]: -30 ... +110
- T[°F]: -22 ... +230



Typical characteristics

Property	Method	Unit	Value
Corrosion effect on copper	DIN 51 811	Grad	1-120
Color		visual	bernstein
Density at 20 °C	ASTM D1122	g/ml	1
Classification	ISO 6743-9	-	ISO-L-X-CCEB2
Worked penetration	DIN ISO 2137	0,1 mm	265 - 295
Dropping point	DIN ISO 2176	°C	>142
Usage temperature		°C	-30 bis +110
Thickener type	-	-	Calcium
VKA welding force	DIN 51 350/4	N	2600
Corrosion protection	DIN 51 802	Korrosionsgrad	0-0
Resistance to water	DIN 51 807/1	-	1-90
Grundölviskosität, 40 °C	ASTM D-7042	mm²/s	750

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

