

HIGHTEC CUT MMU 15

All-purpose, water-immiscible cooling lubricant

Description

HIGHTEC CUT MMU 15 is based on premium base oils and contains additives that effectively lubricate and are anti-corrosive in nature.

Field of application:

- Machining

- Easier forming processes

HIGHTEC CUT MMU 15 is suitable for machining NE metals and soft to hard and tough steels.

Application

HIGHTEC CUT MMU 15 is used undiluted and can be applied with all common application systems.

Advantages

- Wide field of application
- Good cooling and wetting characteristics
- High performance
- Low tendency to evaporate
- Good corrosion protection
- Good surface quality and dimensional stability
- Good rinsing effect
- Inhibits non-ferrous metals

Notes

- Storage:
 - When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 36 months
 - Temperature range: 0- 40°C
 -
- Degreasing:
 - HIGHTEC CUT MMU 15 can be degreased using conventional degreasing media, for example by spray cleaning or immersion cleaning with aqueous-alkaline cleaning agents.



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.867
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	15
Viscosity index	ASTM D2270	-	132
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>170

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

