

HIGHTEC COOL SSH 1

Water-miscible cooling lubricant for carbide grinding without mineral oils

Description

HIGHTEC COOL SSH 1 is a mineral oil-free, water-miscible cooling lubricant that has been developed specifically for grinding of carbide materials. HIGHTEC COOL SSH 1 does not contain any easily nitrosatable amines. HIGHTEC COOL SSH 1 is well tolerated by the skin and provides good corrosion protection.

Application

HIGHTEC COOL SSH 1 is mixed by slowly pouring and stirring into the potable water provided. The mixture produces an odourless and stable solution.

Advantages

- High lubricating performance
- Prevention of cobalt complex formation
- Very stable solution (long product life)
- Low tendency to foam
- Good wetting and flushing action
- High corrosion protection
- Skin-friendly
- Chlorine-free

Recommendation

Particularly suitable for grinding carbides, steel and cast iron.
Recommended concentration to be used: Grinding of carbides and steel > 3% Grinding of cast iron > 4% Mixing temperature range: 15-25°C

Notes

- Storage
- When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 9 months
- Temperature range: 10-35°C



Typical characteristics

Property	Method	Unit	Value
Density at 20 °C	ASTM D1122	g/ml	1.12
Refractometer factor	-	-	2,3
Corrosion protection (chip test) grade 0	DIN 51360/2	%	3
pH of a 10% emulsion	DIN 51369	-	9,3
pH of a 2% emulsion	-	-	9,1

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

