

## HIGHTEC DEFOAMER-A

De-foaming agent for aqueous working fluids

### Description

HIGHTEC DEFOAMER-A is an effective de-foaming agent for water-miscible cooling lubricants with or without mineral oils. HIGHTEC DEFOAMER-A is free of secondary alkanol amines and biocides containing amines.

### Application

HIGHTEC DEFOAMER-A is premixed with water or the emulsion ready for use and added to the system where there is sufficient turbulence for adequate mixing (but not in front of the filter). The de-foaming agent is added in portions.

### Advantages

- Pronounced de-foaming properties
- Low consumption
- High effectiveness

### Recommendation

Recommended concentration to be used: 0.01-0.02% (maximum concentration to be used: 0.05%)

### Notes

- Storage
- When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 2 months
- Temperature range: 10-40°C



## Typical characteristics

Property	Method	Unit	Value
Density at 20 °C	ASTM D1122	g/ml	1.063

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply ([www.rowe-oil.com](http://www.rowe-oil.com)).

