

HIGHTEC FORM SSU 10

Açıklama

Buharlaşan, yüksek alaşimli evrensel şekillendirme yağı. 31'inci BImSchV'ye (VOC Yönetmeliği) tabi değildir ve bu nedenle solvent dengesinde dikkate alınması gerekmez. Alüminyum, demir dışı metaller, paslanmaz çelik ve çelik için uygundur.

Tipik özellikler

Özellik	Metot	Birim	Değer
15 °C'de yoğunluk	ASTM D-7042	g/ml	0.856
Parlama noktası	ASTM D-92 / DIN EN ISO 2592	°C	>100

Bu özellikler mevcut üretim için tipik özelliklerdir. Veriler, özellikler için bir güvence olmayıp özel bir uygulamaya da uygunluk garantisi de oluşturmaz. Ürünlerin elleçlenmesi ve kullanımını etkileyen yürürlükteki yasal hükümler ve yönetmelikler ürünün alıcıları tarafından dikkate alınması gerekir. Rowe, bu ürün bilgisi içindeki tüm teknik verileri önceden bildirim yapmadan değiştirme hakkına sahiptir. Yürürlükteki Genel Teslimat ve Ödeme şartlarını geçerlidir ve uygulanır (www.rowe-oil.com). . The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).