

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 1 of 16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

HIGHTEC RACING MOTOR OIL SAE 10W-60

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil

**1.3. Details of the supplier of the safety data sheet**

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

**1.4. Emergency telephone number:**

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

Classification procedure (H317): Test results

**2.2. Label elements****Regulation (EC) No 1272/2008****Special labelling**

EUH208	Contains C14-C16-C18 Alkylphenole, long chain alkyl thio carbamide metal complex (international CAS 9063-89-2). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 2 of 16

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
112-41-4	1-Dodecene			60 - < 100 %
	203-968-4		01-2119475509-26	
	Asp. Tox. 1; H304 EUH066			
157707-86-3	Dec-1-ene, trimers, hydrogenated (international CAS 68037-01-4)			5 - < 15 %
	500-393-3		01-2119493949-12	
	Asp. Tox. 1; H304			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified (Note L)			1 - < 2.5 %
	265-159-2	649-469-00-9	01-2119480132-48	
	Asp. Tox. 1; H304			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			1 - < 2.5 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			1 - < 2.5 %
	265-169-7	649-474-00-6	01-2119471299-27	
	Asp. Tox. 1; H304			
64742-70-7	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil - unspecified (Note L)			1 - < 2.5 %
	265-174-4	649-477-00-2	01-2119487080-42	
	Asp. Tox. 1; H304			
1190625-94-5	C14-C16-C18 Alkylphenole			1 - < 2.5 %
	931-468-2		01-2119498288-19	
	Skin Sens. 1, STOT RE 2; H317 H373			
	long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)			0.1 - < 0.3 %
	457-320-2		01-0000019337-66	
	Skin Irrit. 2, Skin Sens. 1B, Aquatic Chronic 3; H315 H317 H412			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 3 of 16

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
112-41-4	203-968-4	1-Dodecene	60 - < 100 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
157707-86-3	500-393-3	Dec-1-ene, trimers, hydrogenated (international CAS 68037-01-4)	5 - < 15 %
		oral: LD50 = > 5000 mg/kg	
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
		inhalation: LC50 = 5,53 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-65-0	265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-70-7	265-174-4	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil - unspecified (Note L)	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
	457-320-2	long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)	0.1 - < 0.3 %
		inhalation: Data lacking (gases); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

**After contact with skin**

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

**After ingestion**

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**
**Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO<sub>2</sub>).

Co-ordinate fire-fighting measures to the fire surroundings.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Non-flammable.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 4 of 16

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Pyrolysis products, toxic.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

**For non-emergency personnel**

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

**For emergency responders**

Wear personal protection equipment (refer to section 8).

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**Other information**

Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

**Advice on protection against fire and explosion**

Usual measures for fire prevention.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

**Hints on joint storage**

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

**Further information on storage conditions**

Keep away from heat.

maximum storage temperature: 80 °C

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 5 of 16

**7.3. Specific end use(s)**

Motor oil

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 6 of 16

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local		5,58 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m <sup>3</sup>
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	local		5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local		1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local		5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
1190625-94-5	C14-C16-C18 Alkylphenole			
Worker DNEL, long-term	inhalation	systemic		1,17 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		0,3 mg/kg bw/day
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local		5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
	long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)			
Worker DNEL, long-term	inhalation	systemic		3,52 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		2,23 mg/kg bw/day
Worker DNEL, long-term	dermal	local		0,075 mg/cm <sup>2</sup>
Consumer DNEL, long-term	oral	systemic		0,5 mg/kg bw/day

### HIGHTEC RACING MOTOR OIL SAE 10W-60

Revision: 02.02.2026

Product code: 20019

Page 7 of 16

Consumer DNEL, long-term	dermal	systemic	1,12 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,038 mg/cm <sup>2</sup>
Consumer DNEL, long-term	inhalation	systemic	1,76 mg/m <sup>3</sup>

#### PNEC values

CAS No	Substance	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)	
	Secondary poisoning	9,33 mg/kg
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	
	Secondary poisoning	9,33 mg/kg
1190625-94-5	C14-C16-C18 Alkylphenole	
	Freshwater	0,1 mg/l
	Freshwater (intermittent releases)	1 mg/l
	Marine water	0,01 mg/l
	Freshwater sediment	4266,16 mg/kg
	Marine sediment	426,62 mg/kg
	Secondary poisoning	3,3 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	852,58 mg/kg
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	
	Secondary poisoning	9,33 mg/kg
	long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)	
	Freshwater	0,081 mg/l
	Marine water	0,008 mg/l
	Freshwater sediment	3449 mg/kg
	Marine sediment	344,9 mg/kg
	Secondary poisoning	20 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0,872 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Individual protection measures, such as personal protective equipment

###### Eye/face protection

Wear eye protection/face protection. (EN 166)

###### Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC RACING MOTOR OIL SAE 10W-60

Revision: 02.02.2026

Product code: 20019

Page 8 of 16

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Thermal hazards

No information available.

#### Environmental exposure controls

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	light brown	
Odour:	characteristic	
		<b>Test method</b>
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	Not readily combustible.	
Lower explosion limits:	not determined	Literatur
Upper explosion limits:	not determined	Literatur
Flash point:	240 °C	DIN ISO 2592
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not applicable	DIN 51369
Viscosity / kinematic: (at 40 °C)	165 mm <sup>2</sup> /s	ASTM D 7042
Water solubility: (at 20 °C)	practically insoluble	
Solubility in other solvents Soluble in hydrocarbons (mineral oil.)		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure: (at 20 °C)	<0,1 hPa	calculated.
Density (at 15 °C):	~ 0,851 g/cm <sup>3</sup>	ASTM D 7042
Relative vapour density:	not determined	
Particle characteristics:	not relevant	

### 9.2. Other information

#### Other safety characteristics

Pour point: -38 °C DIN EN ISO 3016

#### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 9 of 16

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

none

**10.5. Incompatible materials**

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

**10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Pyrolysis products, toxic.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-41-4	1-Dodecene				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
157707-86-3	Dec-1-ene, trimers, hydrogenated (international CAS 68037-01-4)				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD Guideline 401
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
	inhalation (4 h) dust/mist	LC50 5,53 mg/l	Ratte	Echa	OECD 403
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
64742-70-7	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
	long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)				
	oral	LD50 >2000 mg/kg	Ratte	Echa	OECD 425
	dermal	LD50 >2000 mg/kg	Kaninchen	Echa	OECD 402
	inhalation	Data lacking			

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

Contains C14-C16-C18 Alkylphenole, long chain alkyl thio carbamide metal complex (international CAS 9063-89-2). May produce an allergic reaction.

Classification procedure (H317): Test results

**Carcinogenic/mutagenic/toxic effects for reproduction**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 11 of 16

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

Inhalation, oral, Skin contact, Eye contact.

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

No information available.

**Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
112-41-4	1-Dodecene					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
	Crustacea toxicity	NOEC 125 mg/l	21 d	Daphnia magna		
157707-86-3	Dec-1-ene, trimers, hydrogenated (international CAS 68037-01-4)					
	Acute fish toxicity	LL50 > 1000 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA	OECD Guideline 201
	Acute crustacea toxicity	EL50 > 1000 mg/l	48 h	Daphnia magna	ECHA	OECD Guideline 202
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 1000 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 10 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia pulex (water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Algae toxicity	NOEC >= 100 mg/l	3 d	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
64742-70-7	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 13 of 16

	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	
long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)							
	Acute crustacea toxicity	EL50	50 mg/l	48 h	Daphnia magna	Echa	OECD 211

**12.2. Persistence and degradability**

CAS No	Chemical name		Value	d	Source
	Method				
	Evaluation				
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified (Note L)				
	OECD 301B		31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)				
	OECD 301B		21 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).				
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)				
	OECD 301F		31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).				

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
157707-86-3	Dec-1-ene, trimers, hydrogenated (international CAS 68037-01-4)	> 6,5
1190625-94-5	C14-C16-C18 Alkylphenole	> 16000000
	long chain alkyl thio carbamide metal complex (international CAS 9063-89-2)	> 5,1

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

**List of Wastes Code - used product**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC RACING MOTOR OIL SAE 10W-60

Revision: 02.02.2026

Product code: 20019

Page 14 of 16

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

#### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

#### 14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

##### Additional information

According to EC directives or the corresponding national regulations the product does not have to be labelled.

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

##### Additional information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 15 of 16

Observe in addition any national regulations!

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,13,15,16.

**Abbreviations and acronyms**

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Irrit. 2: Skin irritation, hazard category 2

Skin Sens. 1: Skin sensitisation, hazard category 1

Skin Sens. 1B: Skin sensitisation, hazard category 1B

STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC RACING MOTOR OIL SAE 10W-60**

Revision: 02.02.2026

Product code: 20019

Page 16 of 16

**Key literature references and sources for data**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H373	May cause damage to liver through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains C14-C16-C18 Alkylphenole, long chain alkyl thio carbamide metal complex (international CAS 9063-89-2). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above data are intended to describe our product in terms of any safety requirements to be observed. They reflect the state of our current knowledge and experience and shall not be construed as warranted characteristics. Any warranty for accuracy and completeness shall be expressly excluded.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*