

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

HIGHTEC RACING CLASSIC SAE 20W-50

UFI: U152-TKEJ-H00U-3C38

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Motor oil

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**Eye Irrit. 2; H319
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008**

Signal word: Warning

Pictograms:

**Hazard statements**H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.**Precautionary statements**P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container to of the disposal according to local regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 2 of 13

2.3. Other hazards

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.
No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
112-41-4	1-Dodecene			5 - < 15 %
	203-968-4		01-2119475509-26	
	Asp. Tox. 1; H304 EUH066			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			1 - < 2.5 %
	265-169-7	649-474-00-6	01-2119471299-27	
	Asp. Tox. 1; H304			
68442-22-8	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts			1 - < 2.5 %
	270-478-5		01-2119948548-22	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411			
122384-87-6	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased			1 - < 2.5 %
	701-251-5		01-2119524004-56	
	Aquatic Chronic 4; H413			
74499-35-7	phenol, (tetrapropenyl) derivatives			< 0.1 %
	616-100-8	604-092-00-9		
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
112-41-4	203-968-4	1-Dodecene	5 - < 15 %
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg		
64742-65-0	265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
68442-22-8	270-478-5	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts	1 - < 2.5 %
	dermal: LD50 = > 2002 mg/kg; oral: LD50 = > 2000 - < 5000 mg/kg		
122384-87-6	701-251-5	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	1 - < 2.5 %
	dermal: LD50 = > 15000 mg/kg; oral: LD50 = > 5000 mg/kg		
74499-35-7	616-100-8	phenol, (tetrapropenyl) derivatives	< 0.1 %
	Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

SECTION 4: First aid measures
4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 3 of 13

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO₂).
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Combustible. Non-flammable.
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 4 of 13

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Further information on handling

maximum process temperature: 100 °C

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.

maximum storage temperature: 80 °C

7.3. Specific end use(s)

Motor oil

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 5 of 13

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
68442-22-8	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts		
Consumer DNEL, long-term	inhalation	systemic	1,98 mg/m ³
Consumer DNEL, long-term	dermal	systemic	5,71 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,24 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	8,05 mg/m ³
Worker DNEL, long-term	dermal	systemic	11,4 mg/kg bw/day
122384-87-6	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased		
Worker DNEL, long-term	inhalation	systemic	3,5 mg/m ³
Worker DNEL, acute	inhalation	systemic	133,6 mg/m ³
Worker DNEL, long-term	dermal	systemic	8,33 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	80 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m ³
Consumer DNEL, acute	inhalation	systemic	0,067 mg/m ³
Consumer DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	50 mg/kg bw/day
74499-35-7	phenol, (tetrapropenyl) derivatives		
Worker DNEL, long-term	inhalation	systemic	0,053 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68442-22-8	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,045 mg/l
Marine water		0,0046 mg/l
Freshwater sediment		0,045 mg/kg
Marine sediment		0,005 mg/kg
Secondary poisoning		10,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,007 mg/kg
122384-87-6	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		5 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1650 mg/kg
Marine sediment		165 mg/kg
Secondary poisoning		11,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		1340 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment
Eye/face protection

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 7 of 13

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	brown	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:		Non-flammable.
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		>200 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic: (at 100 °C)		~ 18,3 mm ² /s
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density (at 15 °C):		0,869 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not relevant

9.2. Other information
Other safety characteristics

Pour point: ~-24 °C

Further Information

No information available.

SECTION 10: Stability and reactivity
10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Heat

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 8 of 13

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

10.6. Hazardous decomposition products

 In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-41-4	1-Dodecene				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
68442-22-8	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts				
	oral	LD50 > 2000 - < 5000 mg/kg	Rat	ECHA	FSHA 16 CFR 1500.3
	dermal	LD50 > 2002 mg/kg	Rat	ECHA	OECD Guideline 402
122384-87-6	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 > 15000 mg/kg	Rabbit	ECHA	OECD 402

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 9 of 13

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

Other information

No information available.

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-41-4	1-Dodecene					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
	Crustacea toxicity	NOEC 125 mg/l	21 d	Daphnia magna		
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia pulex (water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Algae toxicity	NOEC >= 100 mg/l	3 d	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
68442-22-8	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts					
	Acute fish toxicity	LC50 46 mg/l	96 h	Cyprinodon variegatus	ECHA	OECD Guideline 203
	Acute algae toxicity	ErC50 21 mg/l	72 h	Desmodesmus subspicatus	ECHA	OECD Guideline 201
	Acute crustacea toxicity	EL50 23 mg/l	48 h	Daphnia magna	ECHA	OECD Guideline 202
	Crustacea toxicity	NOEC 0,4 mg/l	21 d	Daphnia magna	ECHA	OECD Guideline 211
	Acute bacteria toxicity	EC50 > 10000 mg/l ()	3 h	activated sludge of a domestic residential sewage	ECHA	OECD Guideline 209

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 10 of 13

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			
	OECD 301F	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
122384-87-6	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased			
	OECD 301B	13,4 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68442-22-8	Phosphorodithioic acid, mixed O, O-bis (2-ethylhexyl and isobutyl) esters, zinc salts	1,67
122384-87-6	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	ca. 9,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)
14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 11 of 13

14.4. Packing group:	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Marine transport (IMDG)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No
14.6. Special precautions for user	
No dangerous good in sense of this transport regulation.	
14.7. Maritime transport in bulk according to IMO instruments	
No dangerous good in sense of this transport regulation.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
phenol, (tetrapropenyl) derivatives

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,13,14,15,16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 12 of 13

Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1C: Skin corrosion, sub-category 1C
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Repr. 1B: Reproductive toxicity, hazard category 1B
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC RACING CLASSIC SAE 20W-50

Revision: 02.02.2026

Product code: 20226

Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)