

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Motor oil

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

Classification procedure H318/H319: By analogy.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard statements**

H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Precautionary statements

P103	Read carefully and follow all instructions.
P273	Avoid release to the environment.
P501	Dispose of contents/container to of the disposal according to local regulations.

2.3. Other hazardsEndocrine disrupting properties: phenol, dodecyl-, branched.
No information available.**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 2 of 15

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			30 - < 60 %
	276-738-4	649-483-00-5	01-2119474889-13	
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts			1 - < 2.5 %
	272-238-5		01-2119657973-23	
	Eye Dam. 1, Aquatic Chronic 2; H318 H411			
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			1 - < 2.5 %
	406-040-9	607-530-00-7	01-0000015551-76	
	Aquatic Chronic 4; H413			
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			1 - < 2.5 %
	701-251-5		01-2119524004-56	
	Aquatic Chronic 4; H413			
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts			0.3 - < 1 %
	682-816-2			
	Skin Sens. 1B; H317			
121158-58-5	phenol, dodecyl-, branched			< 0.1 %
	310-154-3	604-092-00-9	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
72623-87-1	276-738-4	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	30 - < 60 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
68784-31-6	272-238-5	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	1 - < 2.5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = 3400 mg/kg		
68784-26-9	701-251-5	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	1 - < 2.5 %
	dermal: LD50 = > 15000 mg/kg; oral: LD50 = > 5000 mg/kg		
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0.1 %
	Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

SECTION 4: First aid measures
4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 3 of 15

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO₂).
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Combustible. Non-flammable.
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 4 of 15

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.

maximum storage temperature: 80 °C

7.3. Specific end use(s)

Motor oil

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 5 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts			
Worker DNEL, long-term		inhalation	systemic	2,93 mg/m ³
Worker DNEL, acute		inhalation	systemic	496,4 mg/m ³
Worker DNEL, long-term		dermal	systemic	10,42 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	100 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	11,75 mg/m ³
Consumer DNEL, acute		inhalation	systemic	198,6 mg/m ³
Consumer DNEL, long-term		dermal	systemic	2,1 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,21 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	29 mg/kg bw/day
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			
Worker DNEL, long-term		inhalation	systemic	6,6 mg/m ³
Worker DNEL, long-term		dermal	systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,62 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,93 mg/kg bw/day
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			
Worker DNEL, long-term		inhalation	systemic	3,5 mg/m ³
Worker DNEL, acute		inhalation	systemic	133,6 mg/m ³
Worker DNEL, long-term		dermal	systemic	8,33 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	80 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m ³
Consumer DNEL, acute		inhalation	systemic	0,067 mg/m ³
Consumer DNEL, long-term		dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	40 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 6 of 15

Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	50 mg/kg bw/day
121158-58-5	phenol, dodecyl-, branched		
Worker DNEL, acute	inhalation	systemic	44,18 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m ³
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 7 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,044 mg/l
Marine water		0,0046 mg/l
Freshwater sediment		0,07 mg/kg
Marine sediment		0,007 mg/kg
Secondary poisoning		8,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,8 mg/l
Soil		0,055 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
Freshwater		0,018 mg/l
Freshwater (intermittent releases)		0,018 mg/l
Marine water		0,002 mg/l
Freshwater sediment		2 mg/kg
Marine sediment		0,2 mg/kg
Secondary poisoning		41,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		10 mg/kg
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		5 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1650 mg/kg
Marine sediment		165 mg/kg
Secondary poisoning		11,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		1340 mg/kg
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (intermittent releases)		0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater sediment		0,226 mg/kg
Marine sediment		0,027 mg/kg
Secondary poisoning		4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,118 mg/kg

8.2. Exposure controls

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 8 of 15



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Not readily combustible.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>210 °C DIN EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic: (at 40 °C)	~ 94,5 mm ² /s ASTM D 7042
Water solubility:	practically insoluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 9 of 15

Density (at 15 °C): ~ 0,863 g/cm³ ASTM D 7042
Relative vapour density: not determined
Particle characteristics: not relevant

9.2. Other information**Other safety characteristics**

Pour point: ~ -30 °C DIN EN ISO 3016

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	ECHA	OECD Guideline 402
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts				
	oral	LD50 3400 mg/kg	Rat	ECHA	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	ECHA	OECD Guideline 402
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 > 15000 mg/kg	Rabbit	ECHA	OECD 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Classification procedure H318/H319: By analogy.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.

Other information

No information available.

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	CONCAWE, Brussels, Belgium (2010)	
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts					
	Acute fish toxicity	LL50 4,4 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD Guideline 203
	Acute algae toxicity	ErC50 410 mg/l	72 h	Desmodesmus subspicatus	ECHA	OECD Guideline 201
	Acute crustacea toxicity	EL50 75 mg/l	48 h	Daphnia magna	ECHA	OECD Guideline 202
	Crustacea toxicity	NOEC 0,4 mg/l	21 d	Daphnia magna	ECHA	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50				
	OECD 301B	13,4 %	28	REACH Dossier	
	Not easily bio-degradable (according to OECD-criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	ca. 4
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	15100000
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	ca. 9,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 12 of 15

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 13 of 15

Substances of very high concern, SVHC (REACH, article 59):

phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 14 of 15

Abbreviations and acronyms

Skin Corr. 1C: Skin corrosion, sub-category 1C
 Eye Dam. 1: Serious eye damage, hazard category 1
 Skin Sens. 1B: Skin sensitisation, hazard category 1B
 Repr. 1B: Reproductive toxicity, hazard category 1B
 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
 Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 10W-40 HC-M

Revision: 02.02.2026

Product code: 20233-998-00

Page 15 of 15

Relevant H and EUH statements (number and full text)

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)