

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Radiator antifreeze

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302
 Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No 1272/2008

Hazard components for labelling

ethanediol; ethylene glycol
 Potassium 3,5,5-trimethylhexanoate

Signal word: Warning

Pictograms:



Hazard statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 2 of 12

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to of the disposal according to local regulations.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
107-21-1	ethanediol; ethylene glycol	30 - < 60 %
	203-473-3	
	603-027-00-1	
	01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373	
93918-10-6	Potassium 3,5,5-trimethylhexanoate	1 - < 2.5 %
	299-890-3	
	Acute Tox. 4, Skin Corr. 1, Eye Dam. 1; H302 H314 H318	
29385-43-1	methyl-1H-benzene triazole	0.1 - < 0.3 %
	249-596-6	
	01-2119979081-35	
	Repr. 2, Acute Tox. 4, Aquatic Chronic 2; H361d H302 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
107-21-1	203-473-3	ethanediol; ethylene glycol	30 - < 60 %
		dermal: LD50 = 10600 mg/kg; oral: LD50 = 4700 mg/kg	
93918-10-6	299-890-3	Potassium 3,5,5-trimethylhexanoate	1 - < 2.5 %
		oral: LD50 = >= 2000 mg/kg	
29385-43-1	249-596-6	methyl-1H-benzene triazole	0.1 - < 0.3 %
		oral: LD50 = 720 mg/kg	

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 3 of 12

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. alcohol resistant foam. Carbon dioxide (CO₂).
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Combustible. Non-flammable.

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 4 of 12

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.
maximum storage temperature: 80 °C

7.3. Specific end use(s)

Lubricating agent, Additive

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
107-21-1	1,2-Dihydroxyethane, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	
107-21-1	Ethylene glycol, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
107-21-1	ethanediol; ethylene glycol			
	Worker DNEL, long-term	inhalation	local	35 mg/m ³
	Worker DNEL, long-term	dermal	systemic	106 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	7 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	53 mg/kg bw/day
29385-43-1	methyl-1H-benzene triazole			
	Worker DNEL, long-term	inhalation	systemic	21,2 mg/m ³
	Worker DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	0,01 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,01 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 5 of 12

PNEC values

CAS No	Substance	Value
Environmental compartment		
107-21-1	ethanediol; ethylene glycol	
Freshwater		10 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		37 mg/kg
Marine sediment		3,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		199,5 mg/l
Soil		1,53 mg/kg
29385-43-1	methyl-1H-benzene triazole	
Freshwater		0,008 mg/l
Freshwater (intermittent releases)		0,086 mg/l
Marine water		0,02 mg/l
Freshwater sediment		0,117 mg/kg
Marine sediment		0,292 mg/kg
Micro-organisms in sewage treatment plants (STP)		39,4 mg/l
Soil		0,0187 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment
Eye/face protection

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 6 of 12

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	magenta	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:	Combustible. Non-flammable.	
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		>100 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value (at 20 °C):		~ 7,5-9 (50%)
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		<0,1 hPa
(at 20 °C)		
Density (at 15 °C):		~ 1,085 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not applicable

9.2. Other information

No information available.

SECTION 10: Stability and reactivity
10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

10.6. Hazardous decomposition products

 In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity

Harmful if swallowed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 7 of 12

ATEmix calculated

ATE (oral) 916,0 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-21-1	ethanediol; ethylene glycol				
	oral	LD50 4700 mg/kg	Rat	GESTIS	
	dermal	LD50 10600 mg/kg	Rabbit	GESTIS	
93918-10-6	Potassium 3,5,5-trimethylhexanoate				
	oral	LD50 >= 2000 mg/kg	Rat	Study report (1986)	OECD Guideline 401
29385-43-1	methyl-1H-benzene triazole				
	oral	LD50 720 mg/kg	Rat	ECHA	OECD Guideline 401

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (ethanediol; ethylene glycol)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards
Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information
12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
93918-10-6	Potassium 3,5,5-trimethylhexanoate					
	Acute algae toxicity	ErC50 mg/l	189,87	72 h	Raphidocelis subcapitata	Study report (2016) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna (Big water flea)	ECHA OECD Guideline 202
29385-43-1	methyl-1H-benzene triazole					
	Acute fish toxicity	LC50	55 mg/l	96 h	Cyprinodon variegatus	ECHA
	Acute algae toxicity	ErC50	75 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	15,8	48 h	Daphnia galeata	ECHA OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	<0,4	21 d	Daphnia magna	ECHA

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
107-21-1	ethanediol; ethylene glycol			
	OECD Guideline 301 C	83	14	
	Readily biodegradable (according to OECD criteria).			
93918-10-6	Potassium 3,5,5-trimethylhexanoate			
	OECD 301B	87,9	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-21-1	ethanediol; ethylene glycol	-1,36
93918-10-6	Potassium 3,5,5-trimethylhexanoate	-0,47
29385-43-1	methyl-1H-benzene triazole	1,079

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations
13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 9 of 12

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

List of Wastes Code - used product

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 10 of 12

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,13,14,15,16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 11 of 12

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
 Skin Irrit. 2: Skin irritation, hazard category 2
 Skin Corr. 1: Skin corrosion, hazard category 1
 Eye Dam. 1: Serious eye damage, hazard category 1
 Eye Irrit. 2: Eye irritation, hazard category 2
 Repr. 2: Reproductive toxicity, hazard category 2
 STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 M-Factor: Multiplication Factor
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 TI: Technical Instructions
 DGR: Dangerous Goods Regulations
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 EG or EC: European Community
 IE: Industrial Emissions
 SVHC: Substance of Very High Concern

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN 13 RM -40 °C

Revision: 02.02.2026

Product code: 21179

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)