

according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Product code: 23012 Revision: 23.06.2025 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC INJECTOR CLEANER DIESEL

UFI: 5X9J-SN3A-P009-54UP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricating agent, Additive

Uses advised against

Fuel additives and fuel components

1.3. Details of the supplier of the safety data sheet

Company name: ROWE Mineralölwerk GmbH

Langgewann 101 Street: D-67547 Worms Place:

Telephone: +49 (0)6241 5906-0 Telefax: +49 (0)6241 5906-999

F-mail· info@rowe-oil.com Contact person: **Product Compliance** E-mail: sdb@rowe-oil.com Internet: www.rowe-oil.com

1.4. Emergency telephone Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 number:

1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbon, C10, aromatic, <1% naphthalene

Signal word: Danger

Pictograms:





Hazard statements

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 2 of 14

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to of the disposal according to local regulations.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Amines, polyethylenepoly-, reaction products with succinic anhydride -

polyisobutenyl derivatives. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC)	No 1272/2008)	·		
64742-47-8	Hydrocarbons, C11-C14, n-alka	anes, isoalkanes, cyclics, <2º	% aromatics	60 - < 100 %	
	926-141-6		01-2119456620-43		
	Asp. Tox. 1; H304 EUH066		·		
112-34-5	2-(2-butoxyethoxy)ethanol; die	hylene glycol monobutyl ethe	er	30 - < 60 %	
	203-961-6	603-096-00-8	01-2119475104-44		
	Eye Irrit. 2; H319	•	·		
64742-94-5	Hydrocarbon, C10, aromatic, <	5 - < 15 %			
	918-811-1		01-2119463583-34		
	STOT SE 3, Asp. Tox. 1, Aquat	ic Chronic 2; H336 H304 H4	11 EUH066		
104-76-7	2-ethylhexan-1-ol	0.3 - < 1 %			
	203-234-3		01-2119487289-20		
	Acute Tox. 4, Skin Irrit. 2, Eye I	rrit. 2, STOT SE 3; H332 H31	15 H319 H335		
84605-20-9	Amines, polyethylenepoly-, rea	0.3 - < 1 %			
	617-593-2				
	Skin Irrit. 2, Skin Sens. 1; H315	5 H317	•		
91-20-3	naphthalene	0.3 - < 1 %			
	202-049-5	601-052-00-2	01-2119561346-37		
	Carc. 2, Acute Tox. 4, Aquatic				

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64742-47-8	926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	60 - < 100 %
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	30 - < 60 %
	dermal: LD50 =	= 4120 mg/kg; oral: LD50 = 5660 mg/kg	
64742-94-5	918-811-1	Hydrocarbon, C10, aromatic, <1% naphthalene	5 - < 15 %
	inhalation: LC5 mg/kg	60 = > 6193 mg/l (vapours); dermal: LD50 = > 3160 mg/kg; oral: LD50 = 3492	
104-76-7	203-234-3	2-ethylhexan-1-ol	0.3 - < 1 %
	inhalation: ATE 3290 mg/kg	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 =	
91-20-3	202-049-5	naphthalene	0.3 - < 1 %
		one = > 77,7 mg/l (vapours); dermal: LD50 = > 16000 mg/kg; oral: LD50 = 710 Acute 1; H400: M=1 c 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet. Foam. Carbon dioxide (CO2).

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 4 of 14

surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

maximum process temperature: 100 °C

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

Keep away from heat.

maximum storage temperature: 80 °C

7.3. Specific end use(s)



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 5 of 14

Lubricating agent, Additive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	
		15	101.2		STEL (15 min)	
104-76-7	2-Ethylhexan-1-ol	1	5.4		TWA (8 h)	
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	
91-20-3	Naphthalene	10	50		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether				
Worker DNEL,	long-term	inhalation	local	67,5 mg/m³	
Worker DNEL,	acute	inhalation	local	101,2 mg/m³	
Consumer DNI	EL, long-term	oral	systemic	6,25 mg/kg bw/day	
64742-94-5	Hydrocarbon, C10, aromatic, <1% naphthalene				
Worker DNEL,	long-term	inhalation	systemic	151 mg/m³	
Worker DNEL,	long-term	dermal	systemic	12,5 mg/kg bw/day	
Consumer DNI	EL, long-term	inhalation	systemic	32 mg/m³	
Consumer DNI	EL, long-term	dermal	systemic	7,5 mg/kg bw/day	
Consumer DNI	EL, long-term	oral	systemic	7,5 mg/kg bw/day	
104-76-7	2-ethylhexan-1-ol				
Worker DNEL,	long-term	inhalation	systemic	12,8 mg/m³	
Worker DNEL,	long-term	inhalation	local	53,2 mg/m³	
Worker DNEL,	acute	inhalation	local	53,2 mg/m³	
Worker DNEL,	long-term	dermal	systemic	23 mg/kg bw/day	
Consumer DNI	EL, long-term	inhalation	systemic	2,3 mg/m³	
Consumer DNI	EL, long-term	inhalation	local	26,6 mg/m³	
Consumer DNI	EL, acute	inhalation	local	26,6 mg/m³	
Consumer DNI	EL, long-term	dermal	systemic	11,4 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	1,1 mg/kg bw/day	
91-20-3	naphthalene				
Worker DNEL, long-term		inhalation	systemic	25 mg/m³	
Worker DNEL,	Worker DNEL, long-term		local	25 mg/m³	
Worker DNEL,	long-term	dermal	systemic	3,57 mg/kg bw/day	



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 6 of 14

PNEC values

CAS No	Substance	
Environment	tal compartment	Value
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	
Freshwater		1,1 mg/l
Freshwater ((intermittent releases)	11 mg/l
Marine wate	r	0,11 mg/l
Freshwater	sediment	4,4 mg/kg
Marine sedir	nent	0,44 mg/kg
Secondary p	poisoning	56 mg/kg
Soil		0,32 mg/kg
104-76-7	2-ethylhexan-1-ol	· .
Freshwater		0,017 mg/l
Freshwater ((intermittent releases)	0,17 mg/l
Marine water		0,002 mg/l
Freshwater sediment		0,284 mg/kg
Marine sediment		0,028 mg/kg
Secondary p	oisoning	55 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	10 mg/l
Soil		0,047 mg/kg
91-20-3	naphthalene	
Freshwater		0,0024 mg/l
Freshwater ((intermittent releases)	0,02 mg/l
Marine water 0,0		0,0024 mg/l
Freshwater sediment 0,067		0,0672 mg/kg
Marine sediment 0,06		0,0672 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	2,9 mg/l
Soil		0,0533 mg/kg

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 7 of 14

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: colourless - light yellow

characteristic Odour: Odour threshold: not determined

Test method

Melting point/freezing point: not determined Boiling point or initial boiling point and > 190 °C

boiling range:

Flammability: Combustible. Vapours can form explosive mixtures with air.

Lower explosion limits: 0,6 vol. % Upper explosion limits: 6 vol. %

74 °C ASTM D 3828 Flash point:

Auto-ignition temperature: not determined Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: < 7 mm²/s Water solubility: practically insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: < 0.2 hPa

(at 20 °C)

Vapour pressure: < 100 hPa

(at 50 °C)

0,848 g/cm³ Density: not determined Relative vapour density: Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Vapours can form explosive mixtures with air.

Oxidizing properties

The product is not: oxidising.

Further Information

No information available.



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 8 of 14

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 9 of 14

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-47-8	Hydrocarbons, C11-C14	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics						
	oral	LD50 mg/kg	> 5000	Rat	ECHA	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rabbit	ЕСНА	OECD Guideline 402		
112-34-5	2-(2-butoxyethoxy)ethan	ol; diethyler	e glycol mor	obutyl ether				
	oral	LD50 mg/kg	5660	Rat				
	dermal	LD50 mg/kg	4120	Rabbit				
64742-94-5	Hydrocarbon, C10, aromatic, <1% naphthalene							
	oral	LD50 mg/kg	3492	Rat	REACh Registration Dossier	OECD Guideline 401		
	dermal	LD50 mg/kg	> 3160	Rabbit	REACh Registration Dossier	OECD Guideline 402		
	inhalation (4 h) vapour	LC50 mg/l	> 6193	Rat	REACh Registration Dossier	OECD Guideline 403		
104-76-7	2-ethylhexan-1-ol							
	oral	LD50 mg/kg	3290	Rat	ECHA	OECD Guideline 401		
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
91-20-3	naphthalene							
	oral	LD50 mg/kg	710	Mouse	ECHA	OECD Guideline 401		
	dermal	LD50 mg/kg	> 16000	Rat	ЕСНА	OECD Guideline 402		
	inhalation (4 h) vapour	LC50 mg/l	> 77,7	Rat	ECHA	EPA TSCA		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Amines, polyethylenepoly-, reaction products with succinic anhydride - polyisobutenyl derivatives. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 10 of 14

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64742-47-8	Hydrocarbons, C11-C14,	n-alkanes,	isoalkanes, cy	clics, <2	2% aromatics		
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	1,22	21 d	Daphnia magna	REACh Registration Dossier	
112-34-5	2-(2-butoxyethoxy)ethano	l; diethylen	e glycol mono	butyl eth	ner		
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus sp.		
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna		
64742-94-5	Hydrocarbon, C10, aroma	atic, <1% na	aphthalene				
	Acute fish toxicity	LL50	14 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	11 mg/l	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201
	Fish toxicity	NOEC mg/l	0,441	28 d	Oncorhynchus mykiss (Rainbow trout)	REACh Registration Dossier	
	Crustacea toxicity	NOEC mg/l	0,771	21 d	Daphnia magna	REACh Registration Dossier	
104-76-7	2-ethylhexan-1-ol						
	Acute fish toxicity	LC50 mg/l	17,1	96 h	Leuciscus idus melanotus	ECHA	EU Method C.1
	Acute algae toxicity	ErC50	11,5 mg/l	72 h	Desmodesmus subspicatus	ECHA	EU Method C.3
	Acute crustacea toxicity	EC50	39 mg/l	48 h	Daphnia magna	ECHA	EU Method C.2
91-20-3	naphthalene						
	Acute algae toxicity	ErC50 mg/l	0,45	72 h	Skeletonema costatum	Mar Environ Res 11, 183-200 (1984)	

12.2. Persistence and degradability



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 11 of 14

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	>= 1,99
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	0,56 (25°C)
64742-94-5	Hydrocarbon, C10, aromatic, <1% naphthalene	>= 3,17
104-76-7	2-ethylhexan-1-ol	2,9
91-20-3	naphthalene	3,4

BCF

CAS No	Chemical name	BCF	Species	Source
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	>= 7		REACh Registration D
64742-94-5	Hydrocarbon, C10, aromatic, <1% naphthalene	>= 70		REACh Registration D
91-20-3	naphthalene	36,5 - 168	Cyprinus carpio	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:
No dangerous good in sense of this transport regulation.
No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 12 of 14

14.3. Transport hazard class(es):14.4. Packing group:No dangerous good in sense of this transport regulation.No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 55, Entry 75

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Product code: 23012 Revision: 23.06.2025 Page 13 of 14

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4 Asp. Tox. 1: Aspiration hazard, hazard category 1 Skin Irrit. 2: Skin irritation, hazard category 2 Eye Irrit. 2: Eye irritation, hazard category 2 Skin Sens. 1: Skin sensitisation, hazard category 1 Carc. 2: Carcinogenicity, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

CLP: Classification, labelling and Packaging

REACH: Registration. Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

EC/EEC: European Community/European Economic Community

EU: European Union

CAS: Chemical Abstracts Service DNFI: Derived No Effect Level DMFI: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

M-factor: Multiplying factor

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association DGR: Dangerous Goods Regulations

ICAO: International Civil Aviation Organization

TI: Technical Instructions

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)



according to Regulation (EC) No 1907/2006

HIGHTEC INJECTOR CLEANER DIESEL

Revision: 23.06.2025 Product code: 23012 Page 14 of 14

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

	<u> </u>
Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
E1111000	

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Amines, polyethylenepoly-, reaction products with succinic anhydride -**EUH208**

polyisobutenyl derivatives. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)