

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

HIGHTEC TOPGEAR SAE 80W-90 HC

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Gear oil

**1.3. Details of the supplier of the safety data sheet**

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

**1.4. Emergency telephone number:**

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

**2.2. Label elements****Regulation (EC) No 1272/2008****Special labelling of certain mixtures**

EUH208	Contains Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched). May produce an allergic reaction.
--------	---

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 2 of 14

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68937-96-2	Polysulfides, di-tert-Bu			2.5 - < 5 %
	273-103-3		01-2119540515-43	
	Skin Sens. 1B, Aquatic Chronic 3; H317 H412			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			1 - < 2.5 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			1 - < 2.5 %
	931-384-6		01-2119493620-38	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H302 H319 H317 H411			
13703-82-7	Magnesium metaborate			0.3 - < 1 %
	237-235-5		01-2120769073-53	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
68937-96-2	273-103-3	Polysulfides, di-tert-Bu	2.5 - < 5 %
		Skin Sens. 1B; H317: $\geq 46 - 100$	
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	1 - < 2.5 %
		dermal: LD50 = $> 5000$ mg/kg; oral: LD50 = $> 5000$ mg/kg	
	931-384-6	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	1 - < 2.5 %
		oral: LD50 = 2000 mg/kg Eye Irrit. 2; H319: $\geq 50 - 100$ Skin Sens. 1B; H317: $\geq 9,39 - 100$	
13703-82-7	237-235-5	Magnesium metaborate	0.3 - < 1 %
		dermal: LD50 = $> 2000$ mg/kg; oral: LD50 = $> 2000$ mg/kg Skin Sens. 1B; H317: $\geq 15 - 100$	

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**After inhalation**

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink 1 glass of water.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 3 of 14

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**5.2. Special hazards arising from the substance or mixture**

Non-flammable.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

**Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Avoid contact with skin, eyes and clothes. Do not breathe mist/vapours/spray.

**For non-emergency personnel**

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

**For emergency responders**

Wear personal protection equipment (refer to section 8).

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****For containment**

Stop leak if safe to do so. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**Other information**

Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

No special measures are necessary.

**Advice on protection against fire and explosion**

No special fire protection measures are necessary.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat,

drink, smoke, sniff. Remove contaminated, saturated clothing immediately. Draw up and observe skin

protection programme. Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat, drink, smoke, sniff.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 80W-90 HC

Revision date: 19.01.2024

Product code: 25000

Page 4 of 14

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed.

##### Hints on joint storage

No special measures are necessary.

#### 7.3. Specific end use(s)

Gear oil

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 5 of 14

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
68937-96-2	Polysulfides, di-tert-Bu		
Worker DNEL, long-term	inhalation	systemic	3,29 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	4,67 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,58 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,167 mg/kg bw/day
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)		
Worker DNEL, long-term	inhalation	systemic	4,28 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,09 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	6,25 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
13703-82-7	Magnesium metaborate		
Worker DNEL, long-term	inhalation	systemic	5,49 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	7,78 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,82 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	0,278 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,28 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 6 of 14

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
68937-96-2	Polysulfides, di-tert-Bu	
Freshwater		0,00024 mg/l
Marine water		0,000024 mg/l
Freshwater sediment		0,94 mg/kg
Marine sediment		0,094 mg/kg
Secondary poisoning		6,66 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,51 mg/l
Soil		0,0181 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)		
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,15 mg/l
Marine water		0,00024 mg/l
Freshwater sediment		0,0129 mg/kg
Marine sediment		0,00129 mg/kg
Secondary poisoning		10 mg/kg
Micro-organisms in sewage treatment plants (STP)		24,33 mg/l
Soil		0,00117 mg/kg
13703-82-7	Magnesium metaborate	
Freshwater		0,05 mg/l
Freshwater (intermittent releases)		0,5 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1,38 mg/kg
Marine sediment		1,38 mg/kg
Secondary poisoning		1,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,247 mg/kg

**8.2. Exposure controls**

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Wear eye/face protection.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the

## HIGHTEC TOPGEAR SAE 80W-90 HC

Revision date: 19.01.2024

Product code: 25000

Page 7 of 14

supplier of these gloves.

### Skin protection

Use of protective clothing.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellow
Odour:	characteristic

#### Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Not readily combustible.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>220 °C ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not applicable DIN 51369
Viscosity / kinematic: (at 100 °C)	~ 15,5 mm <sup>2</sup> /s DIN 51562
Water solubility: (at 20 °C)	practically insoluble
Solubility in other solvents Soluble in hydrocarbons (mineral oil.)	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	<0,1 hPa calculated.
Density (at 15 °C):	~ 0,881 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not relevant

### 9.2. Other information

#### Other safety characteristics

Pourpoint::	~ -21 °C DIN ISO 3016
-------------	-----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

none

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 8 of 14

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) 114207 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)				
	oral	LD50 2000 mg/kg	Rat	REACH Dossier	OECD 401
13703-82-7	Magnesium metaborate				
	oral	LD50 > 2000 mg/kg	Rat	REACH Dossier	OECD 420
	dermal	LD50 > 2000 mg/kg	Rat	REACH Dossier	OECD 402

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

Contains Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched). May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No data available.

**11.2. Information on other hazards**
**Other information**

No information available.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 9 of 14

**Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information**
**12.1. Toxicity**

Based on available data, the classification criteria are not met.

528011722.B170042

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
68937-96-2	Polysulfides, di-tert-Bu					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Algae	Pre-supplier/manufacturer	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 1000 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)					
	Acute fish toxicity	LC50 8,5 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 6,4 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Crustacea toxicity	NOEC 0,12 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68937-96-2	Polysulfides, di-tert-Bu			
	OECD 301B	13 %	28	Pre-supplier/manufacturer
	Not easily bio-degradable (according to OECD-criteria).			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
	OECD 301B	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			
	OECD 301B	7,4 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			

**12.3. Bioaccumulative potential**

The product has not been tested.

### HIGHTEC TOPGEAR SAE 80W-90 HC

Revision date: 19.01.2024

Product code: 25000

Page 10 of 14

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68937-96-2	Polysulfides, di-tert-Bu	5,6
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	< 0,3

#### BCF

CAS No	Chemical name	BCF	Species	Source
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	436	Onchorhynchus mykiss	REACH Registration D

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

##### List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

##### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 3082

##### 14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

##### 14.3. Transport hazard class(es):

9

##### 14.4. Packing group:

III

Hazard label:

9



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 80W-90 HC

Revision date: 19.01.2024

Product code: 25000

Page 11 of 14

Classification code: M6  
 Special Provisions: 274 335 375 601  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 90  
 Tunnel restriction code: -

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Classification code: M6  
 Special Provisions: 274 335 375 601  
 Limited quantity: 5 L  
 Excepted quantity: E1

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Special Provisions: 274 335 969  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-A, S-F

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Special Provisions: A97 A158 A197 A215  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y964  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 964  
 IATA-max. quantity - Passenger: 450 L  
 IATA-packing instructions - Cargo: 964  
 IATA-max. quantity - Cargo: 450 L

#### 14.5. Environmental hazards

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 12 of 14

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive  
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**Additional information**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 80W-90 HC

Revision date: 19.01.2024

Product code: 25000

Page 13 of 14

#### Abbreviations and acronyms

Acute Tox: Acute toxicity  
 Asp. Tox: Aspiration hazard  
 Eye Irrit: Eye irritation  
 Skin Sens: Skin sensitisation  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%  
 CLP: Classification, labelling and Packaging  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 UN: United Nations  
 DNEL: Derived No Effect Level  
 DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety  
 assessment, chapter R.20 (Table of terms and abbreviations).

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched). May produce an allergic reaction.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 80W-90 HC**

Revision date: 19.01.2024

Product code: 25000

Page 14 of 14

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above data are intended to describe our product in terms of any safety requirements to be observed. They reflect the state of our current knowledge and experience and shall not be construed as warranted characteristics. Any warranty for accuracy and completeness shall be expressly excluded.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*