

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 75W-90 HC-LS

Revision: 11.02.2026

Product code: 25004

Page 1 of 18

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

HIGHTEC TOPGEAR SAE 75W-90 HC-LS

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Gear oil

##### 1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

##### 1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Skin Sens. 1; H317  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

Polysulfides, di-tert-Bu  
Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)  
Amines, C10-14-tert-alkyl  
Magnesium metaborate

Signal word: Warning

Pictograms:



###### Hazard statements

H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

###### Precautionary statements

P102 Keep out of reach of children.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves and eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of Water and soap.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 2 of 18

P501

Dispose of contents/container to of the disposal according to local regulations.

**2.3. Other hazards**

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)	15 - < 30 %
	265-157-1	
	649-467-00-8	
	01-2119484627-25	
	Asp. Tox. 1; H304	
63150-07-2	2-Propenoic acid, 2-methyl-, C10-20-alkyl esters, polymers with Methyl methacrylate	5 - < 15 %
	Eye Irrit. 2; H319	
68937-96-2	Polysulfides, di-tert-Bu	2.5 - < 5 %
	273-103-3	
	01-2119540515-43	
	Skin Sens. 1B, Aquatic Chronic 3; H317 H412	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	2.5 - < 5 %
	276-737-9	
	649-482-00-X	
	01-2119474878-16	
	Asp. Tox. 1; H304	
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	1 - < 2.5 %
	931-384-6	
	01-2119493620-38	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H302 H319 H317 H411	
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
	265-169-7	
	649-474-00-6	
	01-2119471299-27	
	Asp. Tox. 1; H304	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
	265-158-7	
	649-468-00-3	
	01-2119487077-29	
	Asp. Tox. 1; H304	
68955-53-3	Amines, C10-14-tert-alkyl	0.3 - < 1 %
	701-175-2	
	01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H400 H410	
13703-82-7	Magnesium metaborate	0.3 - < 1 %
	237-235-5	
	01-2120769073-53	
	Skin Sens. 1B; H317	
74499-35-7	phenol, (tetrapropenyl) derivatives	< 0.1 %
	616-100-8	
	604-092-00-9	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410	

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 3 of 18

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)	15 - < 30 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
68937-96-2	273-103-3	Polysulfides, di-tert-Bu	2.5 - < 5 %
		Skin Sens. 1B; H317: >= 46 - 100	
72623-86-0	276-737-9	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	2.5 - < 5 %
		inhalation: LC50 = 5,53 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
	931-384-6	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	1 - < 2.5 %
		oral: LD50 = 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin Sens. 1B; H317: >= 9,39 - 100	
64742-65-0	265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
68955-53-3	701-175-2	Amines, C10-14-tert-alkyl	0.3 - < 1 %
		inhalation: LC50 = 1,19 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = 552 mg/kg	
13703-82-7	237-235-5	Magnesium metaborate	0.3 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Skin Sens. 1B; H317: >= 15 - 100	
74499-35-7	616-100-8	phenol, (tetrapropenyl) derivatives	< 0.1 %
		Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

**After contact with skin**

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

**After ingestion**

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 4 of 18

**Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO<sub>2</sub>).  
Co-ordinate fire-fighting measures to the fire surroundings.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Non-flammable.  
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Pyrolysis products, toxic.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

**For non-emergency personnel**

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

**For emergency responders**

Wear personal protection equipment (refer to section 8).

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**Other information**

Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

**Advice on protection against fire and explosion**

Usual measures for fire prevention.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 5 of 18

**Hints on joint storage**

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

**Further information on storage conditions**

Keep away from heat.

maximum storage temperature: 80 °C

**7.3. Specific end use(s)**

Gear oil

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

## HIGHTEC TOPGEAR SAE 75W-90 HC-LS

Revision: 11.02.2026

Product code: 25004

Page 6 of 18

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
68937-96-2	Polysulfides, di-tert-Bu			
Worker DNEL, long-term	inhalation	systemic	3,29 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	4,67 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	0,58 mg/m <sup>3</sup>	
Consumer DNEL, long-term	dermal	systemic	1,67 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,167 mg/kg bw/day	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,74 mg/kg bw/day	
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>	
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 7 of 18

	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)		
Worker DNEL, long-term	inhalation	systemic	4,28 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,09 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	6,25 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
68955-53-3	Amines, C10-14-tert-alkyl		
Worker DNEL, long-term	inhalation	systemic	12,5 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	12,1 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	2,5 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	1,2 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,35 mg/kg bw/day
13703-82-7	Magnesium metaborate		
Worker DNEL, long-term	inhalation	systemic	5,49 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	7,78 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,82 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	0,278 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,28 mg/kg bw/day
74499-35-7	phenol, (tetrapropenyl) derivatives		
Worker DNEL, long-term	inhalation	systemic	0,053 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 8 of 18

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68937-96-2	Polysulfides, di-tert-Bu	
Freshwater		0,00024 mg/l
Marine water		0,000024 mg/l
Freshwater sediment		0,94 mg/kg
Marine sediment		0,094 mg/kg
Secondary poisoning		6,66 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,51 mg/l
Soil		0,0181 mg/kg
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,15 mg/l
Marine water		0,00024 mg/l
Freshwater sediment		0,0129 mg/kg
Marine sediment		0,00129 mg/kg
Secondary poisoning		10 mg/kg
Micro-organisms in sewage treatment plants (STP)		24,33 mg/l
Soil		0,00117 mg/kg
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68955-53-3	Amines, C10-14-tert-alkyl	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,004 mg/l
Marine water		0 mg/l
Freshwater sediment		2,14 mg/kg
Marine sediment		0,214 mg/kg
Secondary poisoning		4,71 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,635 mg/l
Soil		0,428 mg/kg
13703-82-7	Magnesium metaborate	
Freshwater		0,05 mg/l

### HIGHTEC TOPGEAR SAE 75W-90 HC-LS

Revision: 11.02.2026

Product code: 25004

Page 9 of 18

Freshwater (intermittent releases)	0,5 mg/l
Marine water	0,05 mg/l
Freshwater sediment	1,38 mg/kg
Marine sediment	1,38 mg/kg
Secondary poisoning	1,67 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	0,247 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye protection/face protection. (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Thermal hazards

No information available.

##### Environmental exposure controls

Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	characteristic
Odour threshold:	not determined

##### Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Not readily combustible.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	> 180 °C ASTM D 92

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 10 of 18

Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not applicable DIN 51369
Viscosity / kinematic: (at 40 °C)	~ 82 mm <sup>2</sup> /s ASTM D 7042
Water solubility: (at 20 °C)	practically insoluble
Solubility in other solvents Soluble in hydrocarbons (mineral oil.)	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	<0,1 hPa calculated.
Density (at 15 °C):	0,868 g/cm <sup>3</sup> ASTM D 7042
Relative vapour density:	not determined
Particle characteristics:	not applicable not relevant

**9.2. Other information**
**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

**Other safety characteristics**

Pour point:

~ -38 °C DIN EN ISO 3016

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**
**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

none

**10.5. Incompatible materials**

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

**10.6. Hazardous decomposition products**

 In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Pyrolysis products, toxic.

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 5000 mg/kg; ATE (dermal) &gt; 5000 mg/kg; ATE (inhalation vapour) &gt; 50 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 11 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
	inhalation (4 h) dust/mist	LC50 5,53 mg/l	Rabbit	echa readacross	OECD
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)				
	oral	LD50 2000 mg/kg	Rat	REACH Dossier	OECD 401
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
68955-53-3	Amines, C10-14-tert-alkyl				
	oral	LD50 552 mg/kg	Mouse	ECHA	OECD Guideline 401
	dermal	LD50 251 mg/kg	Rat	ECHA	OECD Guideline 402
	inhalation (4 h) vapour	LC50 1,19 mg/l	Rat	ECHA	OECD Guideline 403
	inhalation dust/mist	ATE 0,05 mg/l			
13703-82-7	Magnesium metaborate				
	oral	LD50 > 2000 mg/kg	Rat	REACH Dossier	OECD 420
	dermal	LD50 > 2000 mg/kg	Rat	REACH Dossier	OECD 402

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

May cause an allergic skin reaction. (Polysulfides, di-tert-Bu; Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched); Amines, C10-14-tert-alkyl; Magnesium metaborate)

**Carcinogenic/mutagenic/toxic effects for reproduction**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 12 of 18

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

Inhalation, oral, Skin contact, Eye contact.

**11.2. Information on other hazards****Endocrine disrupting properties**

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. No information available.

**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 10 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
68937-96-2	Polysulfides, di-tert-Bu					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Algae	Pre-supplier/manu facturer	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Algae toxicity	NOEC >= 100 mg/l	3 d	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Crustacea toxicity	NOEC > 10 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)					
	Acute fish toxicity	LC50 8,5 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 6,4 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Crustacea toxicity	NOEC 0,12 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia pulex (water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Algae toxicity	NOEC >= 100 mg/l	3 d	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 14 of 18

	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC mg/l	> 1000	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
68955-53-3	Amines, C10-14-tert-alkyl						
	Acute algae toxicity	ErC50 mg/l	0,44	72 h	Pseudokirchneriella subcapitata	ECHA	OECD Guideline 201
	Fish toxicity	NOEC mg/l	0,078	96 d	Oncorhynchus mykiss	ECHA	OECD Guideline 210

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
	OECD 301B	21 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
68937-96-2	Polysulfides, di-tert-Bu			
	OECD 301B	13 %	28	Pre-supplier/manufactur er
	Not easily bio-degradable (according to OECD-criteria).			
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			
	OECD 301F	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			
	OECD 301B	7,4 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			
	OECD 301F	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			
	OECD 301B	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
68937-96-2	Polysulfides, di-tert-Bu	5,6
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	< 0,3
68955-53-3	Amines, C10-14-tert-alkyl	2,9

**BCF**

CAS No	Chemical name	BCF	Species	Source
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	436	Oncorhynchus mykiss	REACH Registration D

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 75W-90 HC-LS

Revision: 11.02.2026

Product code: 25004

Page 15 of 18

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

#### 12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### **List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

##### **List of Wastes Code - used product**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

##### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

#### **Inland waterways transport (ADN)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

#### **Marine transport (IMDG)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

#### **Air transport (ICAO-TI/IATA-DGR)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 75W-90 HC-LS

Revision: 11.02.2026

Product code: 25004

Page 16 of 18

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

No information available.

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):  
phenol, (tetrapropenyl) derivatives

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

##### **Additional information**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

##### **Additional information**

Observe in addition any national regulations!

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,13,15,16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**HIGHTEC TOPGEAR SAE 75W-90 HC-LS**

Revision: 11.02.2026

Product code: 25004

Page 17 of 18

**Abbreviations and acronyms**

Acute Tox. 2: Acute toxicity, hazard category 2  
Acute Tox. 3: Acute toxicity, hazard category 3  
Acute Tox. 4: Acute toxicity, hazard category 4  
Asp. Tox. 1: Aspiration hazard, hazard category 1  
Skin Corr. 1B: Skin corrosion, sub-category 1B  
Skin Corr. 1C: Skin corrosion, sub-category 1C  
Eye Dam. 1: Serious eye damage, hazard category 1  
Eye Irrit. 2: Eye irritation, hazard category 2  
Skin Sens. 1: Skin sensitisation, hazard category 1  
Skin Sens. 1A: Skin sensitisation, hazard category 1A  
Skin Sens. 1B: Skin sensitisation, hazard category 1B  
Repr. 1B: Reproductive toxicity, hazard category 1B  
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
RID: Regulations concerning the international carriage of dangerous goods by rail  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
EmS: Emergency Schedules  
MFAG: Medical First Aid Guide  
ICAO: International Civil Aviation Organization  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
SVHC: Substance of Very High Concern  
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HIGHTEC TOPGEAR SAE 75W-90 HC-LS

Revision: 11.02.2026

Product code: 25004

Page 18 of 18

#### Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above data are intended to describe our product in terms of any safety requirements to be observed. They reflect the state of our current knowledge and experience and shall not be construed as warranted characteristics. Any warranty for accuracy and completeness shall be expressly excluded.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*