

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

HIGHTEC VINTAGE SAE 140

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Gear oil

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P103	Read carefully and follow all instructions.
P273	Avoid release to the environment.
P501	Dispose of contents/container to of the disposal according to local regulations.

Special labelling

EUH208 Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 2 of 12

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68511-50-2	1-propene, 2-methyl, sulphurised			1 - < 2.5 %
	270-943-2			
	Aquatic Chronic 4; H413			
68955-53-3	Amines, C10-14-tert-alkyl			< 0.1 %
	701-175-2		01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H400 H410			
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)			< 0.1 %
	627-034-4		01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68955-53-3	701-175-2	Amines, C10-14-tert-alkyl	< 0.1 %
	inhalation: LC50 = 1,19 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = 552 mg/kg		
1213789-63-9	627-034-4	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)	< 0.1 %
	oral: LD50 = 1689 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 3 of 12

5.1. Extinguishing media**Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO₂).
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Combustible. Non-flammable.
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Further information on handling

maximum process temperature: 100 °C

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 4 of 12

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.

maximum storage temperature: 80 °C

7.3. Specific end use(s)

Gear oil

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-62-7	Residual oils (petroleum), solvent-dewaxed; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
68955-53-3	Amines, C10-14-tert-alkyl			
Worker DNEL, long-term		inhalation	systemic	12,5 mg/m ³
Worker DNEL, long-term		inhalation	local	12,1 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m ³
Consumer DNEL, long-term		inhalation	local	1,2 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,35 mg/kg bw/day
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)			
Worker DNEL, long-term		inhalation	systemic	0,38 mg/m ³
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Worker DNEL, acute		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,035 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,04 mg/kg bw/day

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 5 of 12

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-62-7	Residual oils (petroleum), solvent-dewaxed; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68955-53-3	Amines, C10-14-tert-alkyl	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,004 mg/l
Marine water		0 mg/l
Freshwater sediment		2,14 mg/kg
Marine sediment		0,214 mg/kg
Secondary poisoning		4,71 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,635 mg/l
Soil		0,428 mg/kg
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)	
Freshwater		0,00026 mg/l
Freshwater (intermittent releases)		0,0016 mg/l
Marine water		0,000026 mg/l
Freshwater sediment		3,76 mg/kg
Marine sediment		0,376 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,55 mg/l
Soil		10 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 6 of 12

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	brown	
Odour:	characteristic	
Odour threshold:	not determined	
		Test method
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:	Not readily combustible.	
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:	>210 °C	ISO 2592
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not applicable DIN 51369
Viscosity / kinematic: (at 100 °C)	~ 28 mm ² /s	DIN 51562
Water solubility: (at 20 °C)		practically insoluble
Solubility in other solvents Soluble in hydrocarbons (mineral oil.)		
Partition coefficient n-octanol/water:		not determined
Vapour pressure: (at 20 °C)	<0,1 hPa	calculated.
Density (at 15 °C):	~ 0,90 g/cm ³	DIN 51757
Relative vapour density:		not determined
Particle characteristics:		not relevant

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 7 of 12

10.6. Hazardous decomposition products

 In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68955-53-3	Amines, C10-14-tert-alkyl				
	oral	LD50 552 mg/kg	Mouse	ECHA	OECD Guideline 401
	dermal	LD50 251 mg/kg	Rat	ECHA	OECD Guideline 402
	inhalation (4 h) vapour	LC50 1,19 mg/l	Rat	ECHA	OECD Guideline 403
	inhalation dust/mist	ATE 0,05 mg/l			
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)				
	oral	LD50 1689 mg/kg	Rat	ECHA	OECD Guideline 401

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards
Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 8 of 12

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68955-53-3	Amines, C10-14-tert-alkyl					
	Acute algae toxicity	ErC50 mg/l	0,44	72 h	Pseudokirchneriella subcapitata	ECHA OECD Guideline 201
	Fish toxicity	NOEC mg/l	0,078	96 d	Oncorhynchus mykiss	ECHA OECD Guideline 210

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68955-53-3	Amines, C10-14-tert-alkyl	2,9
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)	5,16

BCF

CAS No	Chemical name	BCF	Species	Source
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines (international CAS 68037-95-6)	173		Environmental Toxicology

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 9 of 12

List of Wastes Code - used product

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

According to EC directives or the corresponding national regulations the product does not have to be labelled.

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 10 of 12

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,13,14,15,16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 11 of 12

Abbreviations and acronyms

Acute Tox. 2: Acute toxicity, hazard category 2
Acute Tox. 3: Acute toxicity, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1B: Skin corrosion, sub-category 1B
Eye Dam. 1: Serious eye damage, hazard category 1
Skin Sens. 1A: Skin sensitisation, hazard category 1A
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC VINTAGE SAE 140

Revision: 02.02.2026

Product code: 25061

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above data are intended to describe our product in terms of any safety requirements to be observed. They reflect the state of our current knowledge and experience and shall not be construed as warranted characteristics. Any warranty for accuracy and completeness shall be expressly excluded.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)