



Safety Data Sheet

ROWE Mineralölwerk GmbH

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC TOPGEAR SAE 75W-80 HC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Gear oil

1.3. Details of the supplier of the safety data sheet

Company name: ROWE Mineralölwerk GmbH
Street: Langgewann 101
Place: D-67547 Worms
Telephone: +49 (0)6241 5906-0
E-mail: info@rowe-oil.com
Contact person: Product Compliance
E-mail: sdb@rowe-oil.com
Internet: www.rowe-oil.com

Telefax: +49 (0)6241 5906-999

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH208 Contains Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched), 2-ethylhexyl methacrylate. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. Other hazards

Endocrine disrupting properties: Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 2 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68037-01-4	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated			5 - < 15 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
	Mineral Oil (CAS 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0) (< 3 % DMSO-extract, IP 346 conform)			2.5 - < 5 %
	Asp. Tox. 1; H304			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			1 - < 2.5 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			1 - < 2.5 %
	931-384-6		01-2119493620-38	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H302 H319 H317 H411			
9036-19-5	Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-			0.1 - < 0.3 %
	618-541-1			
	Eye Irrit. 2, Aquatic Chronic 2; H319 H411			
688-84-6	2-ethylhexyl methacrylate			0.1 - < 0.3 %
	211-708-6		01-2119490166-35	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1B, STOT SE 3, Aquatic Chronic 3; H315 H319 H317 H335 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68037-01-4	500-183-1	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	5 - < 15 %
	oral: LD50 = > 5000 mg/kg		
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	1 - < 2.5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
	931-384-6	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	1 - < 2.5 %
	oral: LD50 = 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin Sens. 1B; H317: >= 9,39 - 100		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 3 of 13

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO2).
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Combustible. Non-flammable.
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO2), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 4 of 13

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Further information on handling

maximum process temperature: 100 °C

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.

maximum storage temperature: 80 °C

7.3. Specific end use(s)

Gear oil

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 5 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)			
Worker DNEL, long-term		inhalation	systemic	4,28 mg/m ³
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,09 mg/m ³
Consumer DNEL, long-term		dermal	systemic	6,25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
688-84-6	2-ethylhexyl methacrylate			
Worker DNEL, long-term		inhalation	systemic	2,5 mg/m ³
Worker DNEL, long-term		dermal	systemic	5 mg/kg bw/day

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,15 mg/l
Marine water		0,00024 mg/l
Freshwater sediment		0,0129 mg/kg
Marine sediment		0,00129 mg/kg
Secondary poisoning		10 mg/kg
Micro-organisms in sewage treatment plants (STP)		24,33 mg/l
Soil		0,00117 mg/kg
688-84-6	2-ethylhexyl methacrylate	
Freshwater		0,003 mg/l
Freshwater (intermittent releases)		0,022 mg/l
Marine water		0 mg/l
Freshwater sediment		2,24 mg/kg
Marine sediment		0,224 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,446 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 7 of 13

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	amber	
Odour:	characteristic	
Odour threshold:	not determined	
		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	Combustible. Non-flammable.	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	> 220 °C	ASTM D 92
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic: (at 40 °C)	53,8 mm ² /s	ASTM D 7042
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 15 °C):	0,854 g/cm ³	ASTM D 7042
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics**Pour point:**

-33 °C ASTM D 97

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 8 of 13

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68037-01-4	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated				
	oral	LD50 mg/kg	> 5000 Rat	ECHA	OECD Guideline 401
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 mg/kg	> 5000 Rat	REACH Dossier	OECD 401
	dermal	LD50 mg/kg	> 5000 Rabbit	REACH Dossier	OECD 402
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)				
	oral	LD50 mg/kg	2000 Rat	REACH Dossier	OECD 401

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched), 2-ethylhexyl methacrylate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 9 of 13

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68037-01-4	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated					
	Acute fish toxicity	LL50 mg/l	> 1000 96 h	Oncorhynchus mykiss	ECHA	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000 96 h	Pseudokirchneriella subcapitata	ECHA	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000 48 h	Daphnia magna	ECHA	OECD Guideline 202
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 mg/l	> 100 96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 mg/l	> 100 72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 mg/l	> 10000 48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC mg/l	>= 1000 14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC mg/l	> 1000 21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)					
	Acute fish toxicity	LC50 mg/l	8,5 mg/l 96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 mg/l	6,4 mg/l 96 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Crustacea toxicity	NOEC mg/l	0,12 21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
688-84-6	2-ethylhexyl methacrylate					
	Acute fish toxicity	LC50 mg/l	2,78 96 h	Oryzias latipes	ECHA	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	7,68 72 h	other algae: Selenastrum capricornutum [now called]	ECHA	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	0,105 21 d	Daphnia magna	ECHA	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 10 of 13

CAS No	Chemical name	Method	Value	d	Source
	Evaluation				
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	OECD 301B	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).				
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	OECD 301B	7,4 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68037-01-4	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	> 6,5
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	< 0,3
688-84-6	2-ethylhexyl methacrylate	4,95

BCF

CAS No	Chemical name	BCF	Species	Source
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	436	Onchorhynchus mykiss	REACH Registration D
688-84-6	2-ethylhexyl methacrylate	37	Danio rerio	ECHA

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 11 of 13

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 12 of 13

SECTION 16: Other information**Abbreviations and acronyms**

Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1B: Skin sensitisation, hazard category 1B
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
EC/EEC: European Community/European Economic Community
EU: European Union
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
M-factor: Multiplying factor
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
DGR: Dangerous Goods Regulations
ICAO: International Civil Aviation Organization
TI: Technical Instructions
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Relevant H and EUH statements (number and full text)

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR SAE 75W-80 HC

Revision: 30.04.2025

Product code: 25203

Page 13 of 13

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched), 2-ethylhexyl methacrylate. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)