



Safety Data Sheet

ROWE Mineralölwerk GmbH

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC TOPGEAR MAX FE SAE 75W-80

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Gear oil

1.3. Details of the supplier of the safety data sheet

Company name: ROWE Mineralölwerk GmbH
Street: Langgewann 101
Place: D-67547 Worms
Telephone: +49 (0)6241 5906-0
E-mail: info@rowe-oil.com
Contact person: Product Compliance
E-mail: sdb@rowe-oil.com
Internet: www.rowe-oil.com

Telefax: +49 (0)6241 5906-999

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH208 Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate.
May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 2 of 13

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|------------|---|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | | | 15 - < 30 % |
| | 265-157-1 | 649-467-00-8 | 01-2119484627-25 | |
| | Asp. Tox. 1; H304 | | | |
| | Mineral Oil (CAS 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0) (< 3 % DMSO-extract, IP 346 conform) | | | 5 - < 15 % |
| | Asp. Tox. 1; H304 | | | |
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | | | 0.3 - < 1 % |
| | 931-384-6 | | 01-2119493620-38 | |
| | Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H302 H319 H317 H411 | | | |
| 80-62-6 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | | | 0.3 - < 1 % |
| | 201-297-1 | 607-035-00-6 | 01-2119452498-28 | |
| | Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|--|---|-------------|
| | Specific Conc. Limits, M-factors and ATE | | |
| 64742-54-7 | 265-157-1 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | 15 - < 30 % |
| | dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg | | |
| | 931-384-6 | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | 0.3 - < 1 % |
| | oral: LD50 = 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin Sens. 1B; H317: >= 9,39 - 100 | | |
| 80-62-6 | 201-297-1 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | 0.3 - < 1 % |
| | inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = ca. 7900 mg/kg | | |

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

After inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 3 of 13

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO2).

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Heating may cause an explosion. In case of warming:

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO2), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 4 of 13

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Further information on handling

maximum process temperature: 100 °C

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.

maximum storage temperature: 80 °C

7.3. Specific end use(s)

Hydraulic fluids, including brake and transmission fluids

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

| CAS No | Substance | ppm | mg/m ³ | fib/cm ³ | Category | Origin |
|---------|--|-----|-------------------|---------------------|---------------|--------|
| 80-62-6 | Methyl methacrylate | 50 | - | | TWA (8 h) | |
| - | Mineral Oil pure, highly & severely refined (Inhalable) | 100 | - | | STEL (15 min) | |
| | | - | 5 | | TWA (8 h) | |

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 5 of 13

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|---|----------------|----------|-------------------------|
| DNEL type | | Exposure route | Effect | Value |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | | | |
| Worker DNEL, long-term | | inhalation | local | 5,58 mg/m ³ |
| Worker DNEL, long-term | | dermal | systemic | 0,97 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 2,73 mg/m ³ |
| Consumer DNEL, long-term | | inhalation | local | 1,19 mg/m ³ |
| Consumer DNEL, long-term | | oral | systemic | 0,74 mg/kg bw/day |
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | | | |
| Worker DNEL, long-term | | inhalation | systemic | 4,28 mg/m ³ |
| Worker DNEL, long-term | | dermal | systemic | 12,5 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 1,09 mg/m ³ |
| Consumer DNEL, long-term | | dermal | systemic | 6,25 mg/kg bw/day |
| Consumer DNEL, long-term | | oral | systemic | 0,25 mg/kg bw/day |
| 80-62-6 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | | | |
| Consumer DNEL, long-term | | dermal | systemic | 8,2 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | local | 1,5 mg/cm ² |
| Consumer DNEL, acute | | dermal | local | 1,5 mg/cm ² |
| Consumer DNEL, long-term | | oral | systemic | 8,2 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 348,4 mg/m ³ |
| Worker DNEL, long-term | | inhalation | local | 208 mg/m ³ |
| Worker DNEL, acute | | inhalation | local | 416 mg/m ³ |
| Worker DNEL, long-term | | dermal | systemic | 13,67 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | local | 1,5 mg/cm ² |
| Worker DNEL, acute | | dermal | local | 1,5 mg/cm ² |
| Consumer DNEL, long-term | | inhalation | systemic | 74,3 mg/m ³ |
| Consumer DNEL, long-term | | inhalation | local | 104 mg/m ³ |
| Consumer DNEL, acute | | inhalation | local | 208 mg/m ³ |

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 6 of 13

PNEC values

| CAS No | Substance | |
|--|---|---------------|
| Environmental compartment | | Value |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | |
| Secondary poisoning | | 9,33 mg/kg |
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | |
| Freshwater | | 0,0024 mg/l |
| Freshwater (intermittent releases) | | 0,15 mg/l |
| Marine water | | 0,00024 mg/l |
| Freshwater sediment | | 0,0129 mg/kg |
| Marine sediment | | 0,00129 mg/kg |
| Secondary poisoning | | 10 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 24,33 mg/l |
| Soil | | 0,00117 mg/kg |
| 80-62-6 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | |
| Freshwater | | 0,94 mg/l |
| Freshwater (intermittent releases) | | 0,94 mg/l |
| Marine water | | 0,094 mg/l |
| Freshwater sediment | | 10,2 mg/kg |
| Marine sediment | | 0,102 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 10 mg/l |
| Soil | | 1,48 mg/kg |

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye protection/face protection. (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 7 of 13

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | | |
|--|-------------------------|--------------------|
| Physical state: | Liquid | |
| Colour: | yellow | |
| Odour: | characteristic | |
| Odour threshold: | not determined | |
| | | Test method |
| Melting point/freezing point: | not determined | |
| Boiling point or initial boiling point and boiling range: | > 316 °C | EN ISO 3405 |
| Flammability: | not determined | |
| Lower explosion limits: | 0,9 vol. % | |
| Upper explosion limits: | 7 vol. % | |
| Flash point: | 200 °C | ASTM D 92 |
| Auto-ignition temperature: | not determined | |
| Decomposition temperature: | not determined | |
| pH-Value: | not determined | |
| Viscosity / kinematic: (at 40 °C) | 54 mm ² /s | |
| Water solubility: | practically insoluble | |
| Solubility in other solvents | | |
| not determined | | |
| Partition coefficient n-octanol/water: | not determined | |
| Vapour pressure: | not determined | |
| Density: | 0,855 g/cm ³ | ISO 3675 |
| Relative density: | 0,855 - 0,861 | |
| Relative vapour density: | not determined | |
| Particle characteristics: | not applicable | |

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive.

Self-ignition temperature

Gas:

ASTM E 659

> 200 °C

Oxidizing properties

The product is not: oxidising.

Other safety characteristics**Pour point:**

-42 °C

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 8 of 13

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | | | | |
|------------|---|---------------|------------------|---|--------------------|
| | Exposure route | Dose | Species | Source | Method |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | | | | |
| | oral | LD50 mg/kg | > 5000 Rat | REACH Dossier | OECD 401 |
| | dermal | LD50 mg/kg | > 5000 Rabbit | REACH Dossier | OECD 402 |
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | | | | |
| | oral | LD50 mg/kg | 2000 Rat | REACH Dossier | OECD 401 |
| 80-62-6 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | | | | |
| | oral | LD50 mg/kg | ca. 7900 Rat | J. Ind. Hyg. Toxicol. 23: 343-351 (1941) | |
| | dermal | LD50 mg/kg | > 5000 Rabbit | ECHA | OECD Guideline 402 |
| | inhalation (4 h) vapour | LC50 | 29,8 mg/l Rat | J. Dent. Res. 59: 1074 (1980) | |

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 9 of 13

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | |
|------------|---|---------------|------------------|---|----------------------------------|-----------------------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | | | | | |
| | Acute fish toxicity | LC50 mg/l | > 100 96 h | Pimephales promelas (fathead minnow) | REACH Dossier | OECD 203 |
| | Acute algae toxicity | ErC50 mg/l | > 100 72 h | Pseudokirchneriella subcapitata | REACH Dossier | OECD 201 |
| | Acute crustacea toxicity | EC50 mg/l | > 10000 48 h | Daphnia magna (Big water flea) | REACH Dossier | OECD 202 |
| | Fish toxicity | NOEC mg/l | >= 1000 14 d | Oncorhynchus mykiss (Rainbow trout) | REACH Dossier | QSAR |
| | Crustacea toxicity | NOEC mg/l | > 10 21 d | Daphnia magna (Big water flea) | REACH Dossier | OECD 211 |
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | | | | | |
| | Acute fish toxicity | LC50 mg/l | 8,5 mg/l 96 h | Pimephales promelas (fathead minnow) | REACH Dossier | OECD 203 |
| | Acute algae toxicity | ErC50 mg/l | 6,4 mg/l 96 h | Pseudokirchneriella subcapitata | REACH Dossier | OECD 201 |
| | Crustacea toxicity | NOEC mg/l | 0,12 21 d | Daphnia magna (Big water flea) | REACH Dossier | OECD 211 |
| 80-62-6 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | | | | | |
| | Acute fish toxicity | LC50 mg/l | > 79 96 h | Oncorhynchus mykiss | REACH Registration Dossier | EPA OTS 797.1400 |
| | Acute crustacea toxicity | EC50 mg/l | 69 mg/l 48 h | Daphnia magna | REACH Registration Dossier | EPA OTS 797.1300 |
| | Fish toxicity | NOEC mg/l | 9,4 mg/l 35 d | Danio rerio | REACH Registration Dossier | OECD Guideline 210 |
| | Crustacea toxicity | NOEC mg/l | 37 mg/l 21 d | Daphnia magna | REACH Registration Dossier | OECD Guideline 211 |

12.2. Persistence and degradability

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 10 of 13

The product has not been tested.

| CAS No | Chemical name | Method | Value | d | Source |
|------------|---|-----------|-------|----|---------------|
| | Evaluation | | | | |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L) | OECD 301B | 21 % | 28 | REACH Dossier |
| | Not easily bio-degradable (according to OECD-criteria). | | | | |
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | OECD 301B | 7,4 % | 28 | REACH Dossier |
| | Not easily bio-degradable (according to OECD-criteria). | | | | |

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|---------|---|---------|
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | < 0,3 |
| 80-62-6 | methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate | 1,38 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|--------|---|-----|----------------------|----------------------|
| | Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) | 436 | Onchorhynchus mykiss | REACH Registration D |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 11 of 13

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 12 of 13

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
EC/EEC: European Community/European Economic Community
EU: European Union
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
M-factor: Multiplying factor
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
DGR: Dangerous Goods Regulations
ICAO: International Civil Aviation Organization
TI: Technical Instructions
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Relevant H and EUH statements (number and full text)

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H302 | Harmful if swallowed. |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

HIGHTEC TOPGEAR MAX FE SAE 75W-80

Revision: 25.11.2025

Product code: 25205

Page 13 of 13

| | |
|--------|--|
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH208 | Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. |
| EUH210 | May produce an allergic reaction. |
| | Safety data sheet available on request. |

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)