

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil

**1.3. Details of the supplier of the safety data sheet**

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

**1.4. Emergency telephone number:**

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

**2.2. Label elements****Regulation (EC) No 1272/2008****Special labelling**

EUH210 Safety data sheet available on request.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 2 of 13

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
2241366-04-9	Octadecene, reaction products with hexadecene, hydrogenated			30 - < 60 %
	832-827-5		01-2120836642-54	
	Asp. Tox. 1; H304			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			2.5 - < 5 %
	265-169-7	649-474-00-6	01-2119471299-27	
	Asp. Tox. 1; H304			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			2.5 - < 5 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			1 - < 2.5 %
	701-251-5		01-2119524004-56	
	Aquatic Chronic 4; H413			
	Alkyl esters of Alkylphenate alkanolic acid			1 - < 2.5 %
	Aquatic Chronic 4; H413			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-65-0	265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	2.5 - < 5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	2.5 - < 5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
68784-26-9	701-251-5	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	1 - < 2.5 %
	dermal: LD50 = > 15000 mg/kg; oral: LD50 = > 5000 mg/kg		

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

**After contact with skin**

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 3 of 13

**After ingestion**

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO<sub>2</sub>).  
Co-ordinate fire-fighting measures to the fire surroundings.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Non-flammable.  
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Pyrolysis products, toxic.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

**For non-emergency personnel**

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

**For emergency responders**

Wear personal protection equipment (refer to section 8).

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**Other information**

Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA

Revision: 02.02.2026

Product code: 4920096

Page 4 of 13

#### Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

#### Advice on protection against fire and explosion

Usual measures for fire prevention.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

##### Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

##### Further information on storage conditions

Keep away from heat.  
maximum storage temperature: 80 °C

#### 7.3. Specific end use(s)

Motor oil

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 5 of 13

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			
Worker DNEL, long-term		inhalation	systemic	3,5 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	133,6 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	8,33 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	80 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	0,067 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	50 mg/kg bw/day

### SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA

Revision: 02.02.2026

Product code: 4920096

Page 6 of 13

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		5 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1650 mg/kg
Marine sediment		165 mg/kg
Secondary poisoning		11,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		1340 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Individual protection measures, such as personal protective equipment

###### Eye/face protection

Wear eye protection/face protection. (EN 166)

###### Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

###### Skin protection

Wear suitable protective clothing.

###### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

###### Thermal hazards

No information available.

###### Environmental exposure controls

Avoid release to the environment.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 7 of 13

**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	No information available.
Odour:	characteristic
Odour threshold:	not determined

**Test method**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Non-flammable.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	242 °C ASTM D 92
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic: (at 40 °C)	93 mm <sup>2</sup> /s ASTM D 7042
Water solubility:	practically insoluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density:	0,845 g/cm <sup>3</sup> ASTM D 7042
Relative vapour density:	not determined
Particle characteristics:	not applicable

**9.2. Other information**
**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

**Other safety characteristics**

Pour point:

-30 °C DIN EN ISO 3016

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**
**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

none

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 8 of 13

**10.5. Incompatible materials**

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

**10.6. Hazardous decomposition products**

 In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Pyrolysis products, toxic.

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**Toxicokinetics, metabolism and distribution**

No data available.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 > 15000 mg/kg	Rabbit	ECHA	OECD 402

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 9 of 13

**Information on likely routes of exposure**

Inhalation, oral, Skin contact, Eye contact.

**11.2. Information on other hazards**
**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information**
**12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
2241366-04-9	Octadecene, reaction products with hexadecene, hydrogenated					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Danio rerio (zebrafish)	ECHA	
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EL50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
	Fish toxicity	NOEC >=100 mg/l	34 d	Gobiocypris rarus (Chinese rare minnow)	ECHA	
	Crustacea toxicity	NOEC 10 mg/l	21 d	Daphnia magna (Big water flea)	ECHA	
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia pulex (water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Algae toxicity	NOEC >= 100 mg/l	3 d	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 1000 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211

**12.2. Persistence and degradability**

The product has not been tested.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 10 of 13

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Note L)			
	OECD 301F	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			
	OECD 301B	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			
	OECD 301B	13,4 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
	Alkyl esters of Alkylphenate alkanolic acid			
	OECD 301B	2 %	28	Pre-supplier/manufacturer
	Not easily bio-degradable (according to OECD-criteria).			

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	ca. 9,3
	Alkyl esters of Alkylphenate alkanolic acid	9,2

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 11 of 13

**List of Wastes Code - used product**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**
**Land transport (ADR/RID)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

**14.7. Maritime transport in bulk according to IMO instruments**

No dangerous good in sense of this transport regulation.

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

**Additional information**

Observe in addition any national regulations!

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA

Revision: 02.02.2026

Product code: 4920096

Page 12 of 13

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,13,15,16.

#### Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1

Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

EC/EEC: European Community/European Economic Community

EU: European Union

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

M-factor: Multiplying factor

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

DGR: Dangerous Goods Regulations

ICAO: International Civil Aviation Organization

TI: Technical Instructions

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

#### Relevant H and EUH statements (number and full text)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**SUNSPEED TRUCKSTAR SAE 10W-40 MULTI-LA**

Revision: 02.02.2026

Product code: 4920096

Page 13 of 13

H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life .
EUH210	Safety data sheet available on request.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*