

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC COOL MMU 1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Metal working fluids

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

2-phenoxyethanol
Alkyl-ether carboxylic acid

Signal word: Danger

Pictograms:



Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 2 of 14

Endocrine disrupting properties: 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate.
No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			30 - < 60 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
68608-26-4	Sulfonic acids, petroleum, sodium salts			5 - < 15 %
	271-781-5		01-2119527859-22	
	Eye Irrit. 2; H319			
122-99-6	2-phenoxyethanol			5 - < 15 %
	204-589-7	603-098-00-9	01-2119488943-21	
	Acute Tox. 4, Eye Dam. 1, STOT SE 3; H302 H318 H335			
53563-70-5	Alkyl-ether carboxylic acid			1 - < 2.5 %
	611-013-1			
	Eye Dam. 1; H318			
55406-53-6	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate			< 0.1 %
	259-627-5	616-212-00-7	01-2120762115-60	
	Acute Tox. 3, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H331 H302 H318 H317 H372 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	30 - < 60 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
68608-26-4	271-781-5	Sulfonic acids, petroleum, sodium salts	5 - < 15 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
122-99-6	204-589-7	2-phenoxyethanol	5 - < 15 %
		dermal: LD50 = > 2000 mg/kg; oral: ATE 1394 mg/kg	
55406-53-6	259-627-5	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	< 0.1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: LD50 = 1795 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 3 of 14

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet. Foam. Carbon dioxide (CO₂).
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Combustible. Non-flammable.
In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains. Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 4 of 14

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place.

Hints on joint storage

Do not store together with: Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

Further information on storage conditions

Keep away from heat.
maximum storage temperature: 80 °C

7.3. Specific end use(s)

Metal working fluids

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 5 of 14

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m ³
Worker DNEL, long-term	inhalation	local		5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil - unspecified (Note L)			
Worker DNEL, long-term	inhalation	local		5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m ³
68608-26-4	Sulfonic acids, petroleum, sodium salts			
Worker DNEL, long-term	inhalation	systemic		0,66 mg/m ³
Worker DNEL, long-term	dermal	systemic		3,33 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic		0,33 mg/m ³
Consumer DNEL, long-term	dermal	systemic		1,667 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic		0,833 mg/kg bw/day
122-99-6	2-phenoxyethanol			
Worker DNEL, long-term	inhalation	systemic		5,7 mg/m ³
Worker DNEL, long-term	inhalation	local		5,7 mg/m ³
Worker DNEL, long-term	dermal	systemic		20,83 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic		2,41 mg/m ³
Consumer DNEL, long-term	inhalation	local		2,41 mg/m ³
Consumer DNEL, long-term	dermal	systemic		10,42 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic		9,23 mg/kg bw/day
Consumer DNEL, acute	oral	systemic		9,23 mg/kg bw/day
55406-53-6	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate			
Worker DNEL, long-term	inhalation	systemic		0,023 mg/m ³
Worker DNEL, acute	inhalation	systemic		0,07 mg/m ³
Worker DNEL, long-term	inhalation	local		1,16 mg/m ³
Worker DNEL, acute	inhalation	local		1,16 mg/m ³
Worker DNEL, long-term	dermal	systemic		2 mg/kg bw/day

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 6 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil - unspecified (Note L)	
Secondary poisoning		9,33 mg/kg
68608-26-4	Sulfonic acids, petroleum, sodium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		723500000 mg/kg
Marine sediment		723500000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		868700000 mg/kg
122-99-6	2-phenoxyethanol	
Freshwater		0,943 mg/l
Freshwater (intermittent releases)		3,44 mg/l
Marine water		0,094 mg/l
Freshwater sediment		7,237 mg/kg
Marine sediment		0,724 mg/kg
Micro-organisms in sewage treatment plants (STP)		36 mg/l
Soil		1,31 mg/kg
55406-53-6	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,001 mg/l
Marine water		0 mg/l
Marine water (intermittent releases)		0,000046 mg/l
Freshwater sediment		0,017 mg/kg
Marine sediment		0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,44 mg/l
Soil		0,005 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection. (EN 166)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 7 of 14

Hand protection

Tested protective gloves must be worn (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Not readily combustible.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>100 °C DIN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value (at 20 °C):	10%ig ~ 9,0 DIN 51369
Viscosity / kinematic: (at 40 °C)	~ 32 mm ² /s DIN 51562
Water solubility:	easily soluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	~ 0,925 g/cm ³ DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not relevant

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 8 of 14

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Oxidizing agent, Reducing agent, Strong acid, Strong alkali.

10.6. Hazardous decomposition products

 In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
68608-26-4	Sulfonic acids, petroleum, sodium salts				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	ECHA	OECD Guideline 402
122-99-6	2-phenoxyethanol				
	oral	ATE 1394 mg/kg			
	dermal	LD50 > 2000 mg/kg	Rabbit		
55406-53-6	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate				
	oral	LD50 1795 mg/kg	Rat	ECHA	OECD Guideline 401
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 9 of 14

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, oral, Skin contact, Eye contact.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 1000 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
68608-26-4	Sulfonic acids, petroleum, sodium salts					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	EPA OTS 797.1050
122-99-6	2-phenoxyethanol					
	Acute fish toxicity	LC50 220 - 460 mg/l	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50 > 500 mg/l	72 h	Scenedesmus sp.		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna		
55406-53-6	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate					
	Acute fish toxicity	LC50 0,41 mg/l	96 h	Cyprinodon variegatus	REACH Dossier	FIFRA Guideline 72-3
	Acute algae toxicity	ErC50 0,022 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Crustacea toxicity	NOEC 0,0499 mg/l	21 d	Daphnia magna	REACH Registration Dossier	EPA OPP 72-4
	Acute bacteria toxicity	EC50 44 mg/l ()	3 h	activated sludge, domestic	REACH Registration Dossier	EU Method C.11

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified (Note L)					
	OECD 301B	31 %	28	REACH Dossier		
	Not easily bio-degradable (according to OECD-criteria).					

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68608-26-4	Sulfonic acids, petroleum, sodium salts	18,05
122-99-6	2-phenoxyethanol	1,16
55406-53-6	3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	2,81

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 11 of 14

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 12 of 14

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,13,15,16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 13 of 14

Abbreviations and acronyms

Acute Tox. 3: Acute toxicity, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC COOL MMU 1

Revision: 02.02.2026

Product code: 65001

Page 14 of 14

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)