

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Motor oil

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE Mineralölwerk GmbH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
E-mail:	info@rowe-oil.com	
Contact person:	Product Compliance	
E-mail:	sdb@rowe-oil.com	
Internet:	www.rowe-oil.com	

1.4. Emergency telephone number:

Ireland: Public (8am-10pm) +353 180 921 66, Healthcare Professionals +353 1809 2566 other Countries: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

Special labelling of certain mixtures

EUH208 Contains 2,5-furandione, polymer with 1-hexadecene, 2-methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4- (phenylamino) phenylimide, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 2 of 13

reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			30 - < 60 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			2.5 - < 5 %
	406-040-9	607-530-00-7	01-0000015551-76	
	Aquatic Chronic 4; H413			
873694-48-5	2,5-furandione, polymer with 1-hexadecene, 2-methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4- (phenylamino) phenylimide			1 - < 2.5 %
	681-947-2			
	Skin Sens. 1, Aquatic Chronic 4; H317 H413			
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts			1 - < 2.5 %
	272-238-5		01-2119657973-23	
	Eye Dam. 1, Aquatic Chronic 2; H318 H411			
1428353-74-5	Coconut oil, reaction products with boric acid (H3BO3), diethanolamine and glycerol			1 - < 2.5 %
	806-731-9		01-2120067755-46	
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411			
	Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated			0.1 - < 0.3 %
	953-650-0			
	Repr. 2, Skin Sens. 1; H361d H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	30 - < 60 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
125643-61-0	406-040-9	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	2.5 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
873694-48-5	681-947-2	2,5-furandione, polymer with 1-hexadecene, 2-methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4- (phenylamino) phenylimide	1 - < 2.5 %
		Skin Sens. 1; H317: >= 5 - 100	
68784-31-6	272-238-5	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = 3400 mg/kg	
	953-650-0	Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	0.1 - < 0.3 %
		Repr. 2; H361d: >= 17,15 - 100	

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 3 of 13

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink 1 glass of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Avoid contact with skin, eyes and clothes. Do not breathe mist/vapours/spray.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Stop leak if safe to do so. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 4 of 13

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

Motor oil

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 5 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			
Worker DNEL, long-term		inhalation	systemic	6,6 mg/m³
Worker DNEL, long-term		dermal	systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,62 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,93 mg/kg bw/day
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts			
Worker DNEL, long-term		inhalation	systemic	2,93 mg/m³
Worker DNEL, acute		inhalation	systemic	496,4 mg/m³
Worker DNEL, long-term		dermal	systemic	10,42 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	100 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	11,75 mg/m³
Consumer DNEL, acute		inhalation	systemic	198,6 mg/m³
Consumer DNEL, long-term		dermal	systemic	2,1 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,21 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	29 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
Freshwater		0,018 mg/l
Freshwater (intermittent releases)		0,018 mg/l
Marine water		0,002 mg/l
Freshwater sediment		2 mg/kg
Marine sediment		0,2 mg/kg
Secondary poisoning		41,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		10 mg/kg
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,044 mg/l
Marine water		0,0046 mg/l
Freshwater sediment		0,07 mg/kg
Marine sediment		0,007 mg/kg
Secondary poisoning		8,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,8 mg/l
Soil		0,055 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
Odour:	characteristic
Melting point/freezing point:	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 7 of 13

Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Not readily combustible.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>210 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic: (at 40 °C)	>20,5 mm²/s
Water solubility:	practically insoluble
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 15 °C):	~ 0,853 g/cm³
Relative vapour density:	not determined
Particle characteristics:	not relevant

9.2. Other information

Other safety characteristics

Pour point: ~ -33 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2005)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2000)	OECD Guideline 402
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts				
	oral	LD50 3400 mg/kg	Rat	Study report (1981)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains 2,5-furandione, polymer with 1-hexadecene, 2-methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4- (phenylamino) phenylimide, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	REACH Dossier	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EL50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	OECD 202
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier	QSAR
	Crustacea toxicity	NOEC > 10 mg/l	21 d	Daphnia magna (Big water flea)	REACH Dossier	OECD 211
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts					
	Acute fish toxicity	LL50 4,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 410 mg/l	72 h	Desmodesmus subspicatus	Study report (2004)	OECD Guideline 201
	Acute crustacea toxicity	EL50 75 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,4 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
	OECD 301B	21 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	15100000
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	ca. 4

BCF

CAS No	Chemical name	BCF	Species	Source
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	38	Cyprinus carpio	Study report (2002)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 10 of 13

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 11 of 13

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,9.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 12 of 13

Abbreviations and acronyms

Asp. Tox: Aspiration hazard
 Skin Irrit: Skin irritation
 Eye Dam: Eye damage
 Eye Irrit: Eye irritation
 Skin Sens: Skin sensitisation
 Repr: Reproductive toxicity
 Aquatic Chronic: Chronic aquatic hazard
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC TRUCKSTAR SAE 5W-30 MULTI-LA

Revision date: 10.02.2024

Product code: 20234

Page 13 of 13

H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains 2,5-furandione, polymer with 1-hexadecene, 2-methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4- (phenylamino) phenylimide, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)